

18.0 V CORDLESS HYDRAULIC CUTTING TOOL



**18.0V
2.0Ah
Li-Ion**

general features

Max cutting Ø mm	Dimensions mm			Battery Li-Ion	Weight kg (with battery)
	length	height	width		
26	436	140	81	18.0V 2.0 Ah	3,4

STORAGE

Type	Dimensions mm	Weight kg	Supplied with the tool	Purchase separately
VAL P48	620x360x138	2,4	✳	—

The tool is supplied as:

- Basic tool with battery and wrist strap
- Spare battery
- Battery charger
- Plastic carrying case suitable for storing the tool and accessories



New

**NEW
18V Li-Ion
BATTERY**



The battery is equipped with LED indicators to show the remaining battery life at any time by pressing the adjacent button. Supplied in a robust plastic case to accommodate the tool and all the accessories. Two batteries and charger included. Operating temperature: -15 to +50 °C

CUTTING CAPACITY - a few examples

Section mm ²	Ø mm	Stranding	CABLE TYPE
120	13,3 mm	-	RIM120
95	-	-	Steel cable with Bitum (DIEPA)
95	18,5 mm	-	Steel cable flex
38,5	7,0	-	Round Steel V2A
78,5	10	-	10mm grounding wire with insulation
50	8,9	7x2,95 mm	Bronze
70	10,3	19 x 2,06 mm	Bronze
95	12,5	19 x 2,50 mm	Bronze
70	10,7	19/2,14	Bronze
95	12,5	19/2,5	Bronze
150	15,75	37/2,25	Bronze
323	23,25	19/4,65	Bronze
415	26,46	37/3,78	Bronze
35/6	8,1	7/2,70	Aluminium-steel
50/8	9,6	7/3,20	Aluminium-steel
50/30	11,7	12/2,33+7/2,33	Aluminium-steel
70/12	11,6	7/1,45+26/1,80	Aluminium-steel
95/15	13,4	7/1,65+26/1,10	Aluminium-steel
150/25	17,3	7/2,15+20/2,70	Aluminium-steel
230/30	21,0	24/3,5+7/2,33	Aluminium-steel
226	19,5	37/2,79	Aluminium-steel
239	20,1	37/2,87	Rope Aluminum Alloy
153	16,0	19/3,2	Cu
16	9,0	126/0,4	Cu flex
70	19,5	2214/0,2	Cu extra flex
120	19,9	608/0,5	Cu flex
240	28,6	1221/0,5	Cu flex
50	11,0	Class 5	Aluminium flex

Can be operated with one hand. Balanced for greater control. Head rotates 180° for ease of operation in confined spaces.

The open head and the "scissor" movement of the blades facilitate the cutting of running cables.

Fitted with a maximum pressure valve.

Extremely quiet, minimal vibration. Durable moulded body offering high resistance to wear and damage in all operating conditions.

New Li-Ion 18V 2Ah High Power battery.