

Palazzoli

General
Catalogue



2019/2020

Palazzoli



CHIAREZZA DELLA FUNZIONE
SEMPLICITÀ DI PROGETTO
QUALITÀ DELLA MANIFATTURA

CLARITY OF FUNCTION
PROJECT SIMPLICITY
QUALITY OF MANUFACTURE





The low voltage industrial socket-outlets of the topTER series are a range of technopolymer wall or flush-mounted products for standard applications, from 16A to 63A, conforming to IEC/EN 60309-1 and IEC/EN 60309-2 standards, available in the IP44 and IP66/IP67 versions.

The flange is provided with reinforcing ribs and in the IP66/IP67 version the gasket is made up of non-ageing elastomer with a restraint system.

The plug inserted signal auxiliary contact makes it ideal for use in industrial automation applications with auxiliary control circuits.

The range is completed by wall-mounting applications in boxes of up to 3 sockets, modular distribution boards of up to 4 sockets and a series of 15° and 90° angled sockets that can be wall-mounted.

Cable features:

Rated current (A)	Poles	Wall-mounted socket entry thread	Wall-mounted socket entry cable diameter (mm)	Entry cable sections (mm ²)
16	2P+⊕	M25	14-18	1 - 2.5
	3P+⊕			
	3P+N+⊕			
32	2P+⊕	M25	14-18	2.5 - 6
	3P+⊕			
	3P+N+⊕			
63	2P+⊕	M40	24-28	4 - 25
	3P+⊕			
	3P+N+⊕			

Compliance with standards	IEC/EN 60309-1 IEC/EN 60309-2
Material	Thermoplastic
Protection rating (IP according to IEC/EN 60529)	IP44 - IP66/IP67
Colour	RAL7035
Contacts material	Nickel-plated brass
Resistance to abnormal heat and fire ("Glow Wire" according to IEC/EN 60695-2-10)	850°C (sockets) 650°C (boxes and boards)
Flammability rating (according to UL94)	V2 (sockets) HB (boxes and boards)
Impact resistance (IK grade according to IEC/EN 62262)	IK08
Rated current	16A - 32A - 63A
Operating Voltage	110V-440V
Operating frequency	50-60Hz
Insulation voltage	690V
Pilot Contact	63A socket-outlets
Storage temperature	-30°C - +70°C
Operating temperature	-25°C - +50°C



Resistance to chemical agents

WATER	SALINE SOLUTION	ACIDS		BASES		SOLVENTS			
		CONCENTRATED	DILUTED	CONCENTRATED	DILUTED	ALCOHOL	ACETONE	PERCHLORO-ETHYLENE	BENZENE
↑	→	↓	→	↑	↑	→	↑	↑	↑
OILS		FATS		AMMONIA	OXIDISERS	INORGANIC SALTS	GASOLINE	DETERGENTS	U.V. RAYS
MINERAL	VEGETABLE	ANIMAL	SYNTHETIC						
↑	↑	↑	↑	↑	↓	↑	↑	↑	↑

Legend: ↑ high resistance → partial resistance ↓ low resistance



Flange for mounting a **fixed flush-mounted socket** on a distribution board **extra low voltage IP66/IP67**

Flange dimensions (mm)	Mountable sockets	Fixing holes spacing (mm)	Palazzoli code	Pack Qty
88x100	extra low voltage CEE	41x41	579849	1

Equipment included: bag with 4 stainless steel screws for fixing the socket.

Technical accessories:



Flange for mounting one **50x50 international domestic socket** in a distribution board **IP54**

Flange dimensions (mm)	Mountable sockets	Fixing holes spacing (mm)	Palazzoli code	Pack Qty
65x83	panel-mounted with flange 50x50	38x38	579848	1

Equipment included: bag with 4 stainless steel screws for fixing the socket.



Flush-mounted **international domestic sockets** dimensions 50x50 **IP54**

Rated current (A)	Rated voltage (V)	Standard	Flange dimensions (mm)	Nation	Palazzoli code	Pack Qty
16	250	DIN49440	50x50	Germany	579845	10
16	250	DIN49440	50x50	Ita/Pol/Hun	579830	10
13	250	BS1363	50x50	United Kingdom	579831	10
16	250	CEE 7/V	50x50	Bel/Fra/Czech Rep.	579832	10

Features: code 579830 with protected receptacles.




Schuko bivalent domestic socket P17/P30 with cap for mounting on a distribution board **IP66**

Description	Flange dimensions (mm)	Pitch	Type	Palazzoli code	Pack Qty
flange with domestic socket 2P+⊕ 10/16A 230V	65 x 83	19	P17/P30	579840	5

Notes: code 579840 is obtained from code 579847 + code 630052.

Technical accessories:



Universal cap for mounting **domoTER** domestic sockets in a distribution board **IP66**


Flange dimensions (mm)	No. of installable modules	Palazzoli code	Pack Qty
65 x 83	2	579847	10



Watertight cap for **plugged-in plug** for mounting **domoTER** sockets in a distribution board **IP66**

Flange dimensions (mm)	No. of installable modules	Palazzoli code	Pack Qty
65 x 83	2	579860	1

Technical accessories:



Recommended use of cap 579860 with topTER distribution boards





Back boxes
for wall-mounting
of topTER devices
IP66/IP67

Entry type	Dimensions (mm)	For flange with dimensions	Palazzoli code	Pack Qty
M25	84 x 100	65 x 83	579750	1
M25	106 x 128	88 x 100	579751	1

Equipment included: cable gland. Stainless steel screws for mounting the sockets. Finishing frames for compact sockets.



Back boxes
for wall-mounting
of 2 topTER devices
IP55

Dimensions (mm)	Total installable devices	Max no. with flange 65x83	Max no. with flange 88x100	Palazzoli code	Pack Qty
103x206	2	2	1	579702	1

Equipment included: stainless steel screws for mounting the sockets. Finishing frames for compact sockets.



Back boxes
for wall-mounting
of 3 topTER devices
IP55

Dimensions (mm)	Total installable devices	Max no. with flange 65x83	Max no. with flange 88x100	Palazzoli code	Pack Qty
116x291	3	3	1	579703	1

Equipment included: stainless steel screws for mounting the sockets. Finishing frames for compact sockets.

Technical accessories:



page 163



Closing flange
for topTER distribution boards
IP66/IP67

Flange dimensions (mm)	Palazzoli code	Pack Qty
65x83	579843	1
88x100	579842	1


Uses: allows closing off the seats of unused sockets.



Equipotential bars
for earth connection

No. of holes	Connection Type	Palazzoli code	Pack Qty
4	M5 screws for wire ends up to 25mm ²	579013	1
10		579014	1


Equipment included: connection screws and fixing brackets.



Auxiliary contact NO+NC
for plug inserted signal

For sockets	Palazzoli code	Pack Qty
topTER fixed and interlocked socket-outlets	579850	1

Equipment included: adaptor for mounting on fixed sockets.






The small domoTER units are a complete range of control devices, sockets and signalling devices. The range consists of devices designed for insertion in protected and watertight boxes with one to three seats. Using suitable technical accessories, domoTER can be mounted on DIN rails and in distribution boards of the topTER series.

Compliance with standards	IEC EN 60669-1 IEC 23-50
Material	Thermoplastic
Protection rating (IP according to IEC/EN 60529)	IP40 - IP55 (boxes) IP66 plugged-in (caps)
Colour	RAL7035
Resistance to abnormal heat and fire ("Glow wire" according to IEC/EN 60695-2-10)	850°C (insert) 650°C (enclosure)
Flammability rating (according to UL94)	V2 (insert) HB (enclosure)
Impact resistance (IK rating according to IEC/EN 62262)	IK08
Insulation class	II □
Storage temperature	-30°C - +70°C
Operating temperature	-15°C - +50°C



USE OF ACCESSORIES



Quick coupling
code 658529



Wall-mounted boxes
for domoTER devices
IP40


Dimensions (mm)	No. of installable modules	Palazzoli code	Pack Qty
76x82x58	1	630001	36
98x82x58	2	630002	36
120x82x58	3	630003	24



Wall-mounted boxes
for domoTER devices
IP55

Dimensions (mm)	No. of installable modules	Palazzoli code	Pack Qty
76x82x58	1	630011	30
98x82x58	2	630012	30
120x82x58	3	630013	24

Technical accessories:



page 41



Universal cap
for mounting **domoTER**
domestic sockets
IP66


Flange dimensions (mm)	No. of installable modules	Palazzoli code	Pack Qty
65 x 83	2	579847	10



Watertight cap
for **plugged-in**
use of mounting
domoTER sockets
IP66

Flange dimensions (mm)	No. of installable modules	Palazzoli code	Pack Qty
65 x 83	2	579860	1

Technical accessories:



page 35



Support
for installing domoTER devices
on DIN rail

Width (mm)	No. of installable modules	Colour	Palazzoli code	Pack Qty
27 (1.5 DIN modules)	1	Grey RAL 7035	630021	20
52 (3 DIN modules)	2		630022	8



Domestic socket
Italian standard
bivalent P11/P17

Rated current (A)	Rated voltage	No. of poles	Type	No. of modules	Palazzoli code	Pack Qty
10/16	250V	2P+⊕	P11/P17	1	630050	20

Features: shuttered receptacles.



Domestic socket
British standard

Rated current (A)	Rated voltage	No. of poles	No. of modules	Palazzoli code	Pack Qty
13	250V	2P+⊕	2	630056	8



Schuko domestic socket
Italian/German standard
bivalent P17/P30

Rated current (A)	Rated voltage	No. of poles	Type	No. of modules	Palazzoli code	Pack Qty
10/16	250V	2P+⊕	P17/P30	2	630052	8

Features: shuttered receptacles.



Domestic socket
French standard

Rated current (A)	Rated voltage	No. of poles	No. of modules	Palazzoli code	Pack Qty
16	250V	2P+⊕	2	630055	8



Schuko domestic socket
Italian/German standard
P30

Rated current (A)	Rated voltage	No. of poles	Type	No. of modules	Palazzoli code	Pack Qty
16	250V	2P+⊕	P30	2	630051	8

Features: shuttered receptacles.



Red Schuko domestic socket
Italian/German standard
P30

Rated current (A)	Rated voltage	No. of poles	Type	No. of modules	Palazzoli code	Pack Qty
16	250V	2P+⊕	P30	2	630053	8

Features: shuttered receptacles.



Red Schuko domestic socket
Italian/German standard bivalent
P17/P30

Rated current (A)	Rated voltage	No. of poles	Type	No. of modules	Palazzoli code	Pack Qty
10/16	250V	2P+⊕	P17/P30	2	630054	8

Features: shuttered receptacles.



Multifunction device
1P or 2P switch
1P two-way switch
NO/NC button
16A 250V

Function (mm)	No. of modules	Palazzoli code	Pack Qty
1P or 2P switch, NO 1P button or 1P two-way switch, 1P NC button	1	630030	20

Complementary products: warning lamp code 630091.

Features: the code 630030 is realised in the "NO button" configuration.


To obtain the switch and two-way switch schemes, remove the spring located underneath the key with a screwdriver and perform the wiring according to the schemes here below.



Intermediate switch
16A 250V

No. of poles	No. of modules	Palazzoli code	Pack Qty
1	1	630031	20

DIAGRAM FOR MULTIFUNCTION DEVICE USE





TV sockets

Standard	No. of modules	Palazzoli code	Pack Qty
TV 9.5 mm final	1	630070	20
TV 9.5 mm through/final	1	630071	20



Rj data sockets

Description	No. of modules	Palazzoli code	Pack Qty
RJ12 6/6 contacts	1	630080	20
RJ45 category 5E	1	630081	20
RJ45 category 6	1	630082	20



USB socket

Description	No. of modules	Palazzoli code	Pack Qty
USB 5V 1A power supply	1	630085	4



Fuse holder
5x20 mm 10A max

Fuse type	No. of modules	Rated current max (A)	Palazzoli code	Pack Qty
5x20mm	1	10A	630035	20



MCB
1P+N C16A Pdl 3kA

Rated current (A)	No. of modules	Palazzoli code	Pack Qty
16	1	630036	20



Signalling lamps
230V - 50/60Hz

Diffuser colour	No. of modules	Palazzoli code	Pack Qty
white	1	630040	20
red	1	630041	20
green	1	630042	20



Closing cap

Description	No. of modules	Palazzoli code	Pack Qty
closing cap	1	630090	100



230V warning lamp
with 100mm cable

No. of modules	Palazzoli code	Pack Qty
1	630091	200

Features: it can be inserted in the multifunction device code 630030 and can be used as a spare part in the domoTER signalling lamps.



Quick coupling
for domoTER boxes

Inner diameter (mm)	Fixing	Palazzoli code	Pack Qty
20	snap	658529	1

Equipment included: with gasket.
Uses: allows to realise multiple box compositions.

The background of the entire page is a night-time satellite view of the Earth, showing the illuminated continents of Europe and Africa. A bright sun or star is positioned at the horizon, creating a lens flare effect with numerous blue and white rays radiating across the scene. A network of blue lines connects various points, resembling a global communication or data network, overlaid on the satellite imagery.

Palazzoli

— excellence —
FROM ITALY

Palazzoli S.p.A
25128 Brescia - Italy - Via F. Palazzoli, 31
Tel +39 030 2015.1
Fax +39 030 2015.258
www.palazzoli.com
export@palazzoli.com
