



DO, DC 24 V, 500 mA

DO 16x DC 24 V, 500 mA

- 24 V DC output voltage
- 500 mA output current per channel
- A blue LED indicates the module's operating status
- Green LEDs (one for each output) indicate the output status
- 16 outputs, electrically isolated from the backplane bus

Technical specifications

General information	
Order number	600-220-0AP21
Article name	DO 16x DC 24 V, 500 mA
Scope of delivery	DO 16x DC 24 V, 500 mA
Dimensions (DxWxH)	110 x 25 x 73 mm
Weight	Approx. 110 g
Number of outputs	16
Electrical isolation	
from the backplane bus	Yes
Between the channels	No
Supply voltage U_p, U_s	
Rated value	24 V DC
Ripple U_{SS}	max. 3.6 V
Permissible range (with ripple)	20 ... 30 V
Voltage for $t < 10$ ms	50 V
Output current	
Rated value	500 mA
Leakage current	Max. 0.5 mA
Current draw	
External	max. 80 mA + Load
Internal	max. 47 mA
Power dissipation	Max. 5 W
Output short-circuit protection	Electronic, for each individual channel
Inductive cutoff voltage limit	-48 V
Hot-swap capable	Yes
Ambient conditions	
Ambient temperature	0 °C ... +60 °C

Transport and storage temperature	-20 °C ... +80 °C
Relative air humidity	95 % r H without condensation
Protection rating	IP 20
Certifications	CE, UL
UL	
Surrounding Air Temperature	0 °C ... +60°C
Pollution degree	2
CE	
Noise immunity	DIN EN 61000-6-2 "EMC Immunity"
Interference emission	DIN EN 61000-6-4 "EMC Emission"
Vibration and shock resistance	DIN EN 60068-2-6:2008 „Vibration“, DIN EN 60068-2-27:2010 „Shock"
RoHS	Yes
REACH	Yes