



TECHNICAL FEATURES

| Crimping Range | PVC, PC and PA6.6 insulated terminals and connectors for conductor sizes 4 to 6 sąmm |
|--------------------|---|
| Dimensions mm | |
| Length | 320 |
| Width | 105 |
| Height | 25 |
| Weight g | 810 |
| Package Dimensions | 330 x 110 x 50 mm |

Professional manual mechanical tool with ratchet mechanism that prevents the handles from opening again before reaching the ratchet. Equipped with a positioning device to reduce the operator's effort and facilitate proper crimping of the conductor.

According to the different thicknesses of the conductor insulation, the crimping on the insulation can be carried out by adjusting the jaws through three different settings: 1) strong, 2) medium, 3) light. The tool is particularly easy to use thanks to its shape and handle coat-



At the end of the crimping the outer surface of the conductor is automatically stamped with the following crimping code:

three points for yellow conductor from 4 to 6 sqmm











Construction features:

- · Special treated and externally protected steel body, ratchet and handles.
- Handle coating in soft yellow PVC plastic.

MECHANICAL TOOLS HP4 RANGE

HP4-C10



TECHNICAL FEATURES

| Crimping Range | For sleeve connectors type C6-C6 and C10-C10 |
|--------------------|---|
| Dimensions mm | |
| Length | 325 |
| Width | 105 |
| Height | 21 |
| Weight g | 730 |
| Package Dimensions | 330 x 110 x 50 mm |









Professional manual mechanical tool with ratchet mechanism that prevents the handles from opening again before reaching the ratchet. The tool is particularly easy to use thanks to its shape and handle coat-

ing.











Construction features:

- · Special treated and externally protected steel body, ratchet and handles.
- Handle coating in soft yellow PVC plastic.