


# S5000M DC Switch - disconnector for DC current

3P + 3P 4P + 4P



Size 2	
A	400 500
	1500 Vdc



## Technical information



According to IEC-EN-UNE 60947-1  
IEC-EN-UNE 60947-3

	3+3	4+4
Rated thermal current in ambient at 40°C	A 400	500
I <sub>th</sub> 50°C	A 400	500
RH 60% 60°C	A 400	500
Rated insulation voltage DC20 Ui	V 1500	1500
Rated dielectric strength 50 Hz., 1 min.	V 8000	8000
Rated impulse withstand voltage U <sub>imp</sub>	kV 12	12
Rated operational current I <sub>e</sub>	DC21B 1500 Vdc	A 400
Rated making capacity 4+4	DC21 1500 Vdc	A - 500




\*(1) Without limiting protective device (short-circuit maintained 50...200 ms.)

\*(2) With limiting protective device which set a limit to peak value short-circuit making capacity and maximum power dissipation to indicated values

## Connection diagram





3P+3P

## Connection diagram



4P+4P

## Connection diagram



tests:



tests:


## Accessories



» Direct handle  
CODE DS-LI22



» Panel handle included shaft \*(e1)  
IP65|UL50E/NEMA 250  
Types: 1, 3R, 4, 4Xy12  
CODE DS-LA22



» Shafts  
Standard shaft included \*(e1)  
L (mm) 239 P (mm) 325...490




» Auxiliary contacts  
1NA+1NC CODE DS-AU11  
2NA+2NC CODE DS-AU12

I<sub>e</sub> = 16 A (resistive loads)  
4 A (inductive loads) at 250 Vac.



» Terminal shrouds (2 units)  
E TOP DS-CU280U C DS-CU200U  
Bottom DS-CU200U DS-CU280U



» Bridging links (2 or 3 units)  
3P+3P 4P+4P  
E DS-PI220U C DS-PI230U  
F DS-PI270U D DS-PI260U

## Dimensions (mm)

