

# ***Palazzoli***

## General Catalogue



2019/2020

# ***Palazzoli***



CHIAREZZA DELLA FUNZIONE  
SEMPlicità DI PROGETTO  
QUALITÀ DELLA MANIFATTURA

---

CLARITY OF FUNCTION  
PROJECT SIMPLICITY  
QUALITY OF MANUFACTURE



# TAIS CUBE



**GOOD DESIGN**  
INTERNATIONAL AWARD



## TAIS CUBE

Resistant to everything thanks to the Palazzoli thermosetting GRP




TAIS Cube has a very high protection rating, IP66. This feature, certified in a laboratory with a 100 l/min water jet test, guarantees the product against strong water jets.



The steel frame allows to easily mount modular devices and trunking, and to comfortably wire everything on the bench, out of the board.

The wired frame can then be easily inserted inside the board. The material of which it is made guarantees robustness and durability over time.



The unique product design provides a wide and spacious enclosure. As a consequence the back plate and door (choose from blind or transparent) offer 15% of extra space available if compared with similar sizes of the major competitors.



The door hinges, made of steel and nickel-plated brass, are located far from the edges to avoid breakage in the case of impact.

Suitable for thermal power plants, cement plants, mineral oil extraction plants, nuclear plants and laboratories, commercial and exhibition activities, airports, photovoltaic installations, railway and underground facilities.



| Size | No. of vertical modules | No. of DIN modules | Outer dimensions | Internal usable dimensions | Distribution board with blind door | Distribution board with transparent door |
|------|-------------------------|--------------------|------------------|----------------------------|------------------------------------|--|
| 1    | -                       | -                  | 260x305x160      | 200x250x100                | 550001                             | 550031                                   |
| 2    | 3                       | 36 (3X12)          | 340x430x180      | 280x375x120                | 550002                             | 550032                                   |
| 3    | 3                       | 54 (3X18)          | 450x505x220      | 390x450x160                | 550003                             | 550033                                   |
| 4    | 4                       | 72 (4X18)          | 450x655x220      | 390x600x160                | 550004                             | 550034                                   |
| 5    | 4                       | 96 (4X24)          | 560x655x260      | 500x600x200                | 550005                             | 550035                                   |
| 6    | 5                       | 140 (5X28)         | 630x810x300      | 570x750x235                | 550006                             | 550036                                   |
| 7    | 5                       | 200 (5X40)         | 850x1060x350     | 790x1000x290               | 550007                             | 550037                                   |

THE REVOLUTIONARY



QUICK COUPLING SYSTEM












fitting the springs

assembling the frame

fitting the frame



| AUTOMATION  |   |   | DISTRIBUTION  |   |   |   |   |   |
|---|---|---|---|---|---|---|---|---|
|  |  |  |  |  |  |  |  |  |
| Back plate in steel   | Back plate in thermosetting GRP   | Inner door in thermosetting GRP   | Click Cube functional frame   | Click Cube windowed panel   | Click Cube blind panel  | Click Cube double blind panel   | Click Cube DIN rail   | Click Cube partial steel plate  |
| 550601  | 550621  | -   | -   | -   | -   | -   | -   | -   |
| 550602  | 550622  | 550502  | 550562  | 550522  | 550542  | 550552  | 550582  | 550632  |
| 550603  | 550623  | 550503  | 550563  | 550523  | 550543  | 550553  | 550583  | 550633  |
| 550604  | 550624  | 550504  | 550564  |   |   |   |   |   |
| 550605  | 550625  | 550505  |   | 550525  | 550545  | 550555  | 550585  | 550635  |
| 550606  | 550626  | 550506  | 550566  | 550526  | 550546  | 550556  | 550586  | 550636  |
| 550607  | -   | 550507  | 550567  | 550527  | 550547  | 550557  | 550587  | 550637  |

| COMMON ACCESSORIES  |                 |   |  |                 |
|---|-----------------|---|--|-----------------|
|  |                 |  |  |                 |
| Set of 4 brackets   |                 | Security lock   | Support for pole mounting  |                 |
| Galvanised  | Stainless steel |   | For sizes 1-2  | For sizes 3-4-5 |
| 550640  | 550641          | 550680  | 550642   | 550643          |



TAIS Cube series distribution and automation boards are a range of products in Palazzoli thermosetting GRP for heavy-duty applications with IP66 protection rating and resistant to UV rays. The system is composed of 7 sizes in each version with blind or transparent door.

The accessories to use the board in typical configurations of automation are the back plate in steel sheet or in thermosetting GRP and the inner door in thermosetting GRP, equipped with opening handles and that can be installed at two different positions and fixed on both sides. In the distribution configuration, the steel frame allows for modular compositions with blind and windowed panels, depth-adjustable DIN rails and partial back plates. All elements are simply fixed with the "Click Cube" snap-in system.

The wiring can be performed on the bench or directly inside the distribution board.

The door is fixed to the back box with elements in nickel-plated brass and stainless steel located far from the edges and that allow an opening wider than 180°.

### WEB - TAIS CUBE

The website dedicated to the distribution and automation boards of the TAIS CUBE series is available at [www.palazzoli.com](http://www.palazzoli.com)



|   |                                    |
|---|------------------------------------|
| Compliance with standards   | <b>IEC/EN 62208</b>                |
| Material  | <b>Palazzoli thermosetting GRP</b> |
| Protection rating (IP according to IEC/EN 60529)                                  | <b>IP66</b>                        |
| Colour  | <b>RAL7035</b>                     |
| Resistance to abnormal heat and fire ("Glow Wire" according to IEC/EN 60695-2-10) | <b>960°C</b>                       |
| Flammability rating (according to UL94)   | <b>V0</b>                          |
| Impact resistance (IK grade according to IEC/EN 62262)                            | <b>IK10</b>                        |
| Rated frequency   | <b>0 - 1000 Hz</b>                 |
| Rated voltage AC  | <b>1000 Vac</b>                    |
| Rated voltage DC  | <b>1500 Vcc</b>                    |
| Rated impulse seal voltage  | <b>8kV</b>                         |
| Maximum short-circuit current Icc   | <b>35kA</b>                        |
| Insulation class  | <b>II □</b>                        |
| Storage temperature   | <b>-50°C - +90°C</b>               |
| Operating temperature   | <b>-30°C - +90°C</b>               |



### Resistance to chemical agents

| WATER   | SALINE SOLUTION | ACIDS        |           | BASES        |           | SOLVENTS        |          |                    |           |
|---------|-----------------|--------------|-----------|--------------|-----------|-----------------|----------|--------------------|-----------|
|         |                 | CONCENTRATED | DILUTED   | CONCENTRATED | DILUTED   | ALCOHOL         | ACETONE  | PERCHLORO-ETHYLENE | BENZENE   |
| ↑       | ↑               | →            | ↑         | ↑            | ↑         | ↑               | ↑        | ↑                  | ↑         |
| OILS    |                 | FATS         |           | AMMONIA      | OXIDISERS | INORGANIC SALTS | GASOLINE | DETERGENTS         | U.V. RAYS |
| MINERAL | VEGETABLE       | ANIMAL       | SYNTHETIC |              |           |                 |          |                    |           |
| ↑       | ↑               | ↑            | ↑         | ↑            | ↑         | ↑               | ↑        | ↑                  | ↑         |

Legend: ↑ high resistance → partial resistance



**Distribution boards**  
in thermosetting GRP  
with **blind door**  
**IP66**

| Size | Outer dimensions (mm) | Usable inner dimensions (mm) | No-load power dissipation (W) | Palazzoli code | Pack Qty |
|------|-----------------------|------------------------------|-------------------------------|----------------|----------|
| 1    | 260x305x160           | 200x250x100                  | 53                            | <b>550001</b>  | 1        |
| 2    | 340x430x180           | 280x375x120                  | 90                            | <b>550002</b>  | 1        |
| 3    | 450x505x220           | 390x450x160                  | 138                           | <b>550003</b>  | 1        |
| 4    | 450x655x220           | 390x600x160                  | 174                           | <b>550004</b>  | 1        |
| 5    | 560x655x260           | 500x600x200                  | 217                           | <b>550005</b>  | 1        |
| 6    | 630x810x300           | 570x750x235                  | 302                           | <b>550006</b>  | 1        |
| 7    | 850x1060x350          | 790x1000x290                 | 506                           | <b>550007</b>  | 1        |

**Equipment included:** key with triangular insert, screw cover caps for double insulation.



**Distribution boards**  
in thermosetting GRP  
with **transparent door**  
**IP66**

| Size | Outer dimensions (mm) | No. of DIN modules | No-load power dissipation (W) | Palazzoli code | Pack Qty |
|------|-----------------------|--------------------|-------------------------------|----------------|----------|
| 1    | 260x305x160           | -                  | 53                            | <b>550031</b>  | 1        |
| 2    | 340x430x180           | 36 (3x12)          | 90                            | <b>550032</b>  | 1        |
| 3    | 450x505x220           | 54 (3x18)          | 138                           | <b>550033</b>  | 1        |
| 4    | 450x655x220           | 72 (4x18)          | 174                           | <b>550034</b>  | 1        |
| 5    | 560x655x260           | 96 (4x24)          | 217                           | <b>550035</b>  | 1        |
| 6    | 630x810x300           | 140 (5x28)         | 302                           | <b>550036</b>  | 1        |
| 7    | 850x1060x350          | 200 (5x40)         | 506                           | <b>550037</b>  | 1        |

**Equipment included:** key with triangular insert, screw cover caps for double insulation.

**Technical accessories:**



page 163



**Back plates**  
in **steel**

| Size | Dimensions (mm) | Palazzoli code | Pack Qty |
|------|-----------------|----------------|----------|
| 1    | 180x240         | <b>550601</b>  | 5        |
| 2    | 260x370         | <b>550602</b>  | 5        |
| 3    | 370x445         | <b>550603</b>  | 5        |
| 4    | 370x595         | <b>550604</b>  | 1        |
| 5    | 475x595         | <b>550605</b>  | 1        |
| 6    | 550x745         | <b>550606</b>  | 1        |
| 7    | 765x995         | <b>550607</b>  | 1        |

**Equipment included:** complete with screws for mounting.



**Back plates**  
in thermosetting GRP

| Size | Dimensions (mm) | Palazzoli code | Pack Qty |
|------|-----------------|----------------|----------|
| 1    | 180x240         | <b>550621</b>  | 5        |
| 2    | 260x370         | <b>550622</b>  | 5        |
| 3    | 370x445         | <b>550623</b>  | 5        |
| 4    | 370x595         | <b>550624</b>  | 1        |
| 5    | 475x595         | <b>550625</b>  | 1        |
| 6    | 550x745         | <b>550626</b>  | 1        |

**Equipment included:** complete with screws for mounting.



**Click Cube reversible**  
**inner doors**  
in thermosetting GRP

| Size | Dimensions (mm) | Palazzoli code | Pack Qty |
|------|-----------------|----------------|----------|
| 2    | 280x375         | <b>550502</b>  | 4        |
| 3    | 388x450         | <b>550503</b>  | 4        |
| 4    | 388x600         | <b>550504</b>  | 4        |
| 5    | 496x600         | <b>550505</b>  | 1        |
| 6    | 568x750         | <b>550506</b>  | 1        |
| 7    | 784x1000        | <b>550507</b>  | 1        |

**Features:** inner-door is reversible and can be easily opened using the appropriate handles. It can be installed at two different depths.



**Click Cube quick-fit functional frames** for the installation of front panels and DIN rails

| Size | Installable panels | Palazzoli code | Pack Qty |
|------|--------------------|----------------|----------|
| 2    | 3                  | <b>550562</b>  | 6        |
| 3    | 3                  | <b>550563</b>  | 6        |
| 4-5  | 4                  | <b>550564</b>  | 6        |
| 6    | 5                  | <b>550566</b>  | 1        |
| 7    | 5                  | <b>550567</b>  | 1        |

**Equipment included:** complete with springs for fastening to the distribution board.  
**Features:** it allows the wiring of the modular panels outside of the board and the installation of DIN rails at different heights.



**Click Cube front windowed panels** with DIN rail for modular devices

| Size | Height (mm) | No. of DIN modules | Palazzoli code | Pack Qty |
|------|-------------|--------------------|----------------|----------|
| 2    | 125         | 12                 | <b>550522</b>  | 6        |
| 3-4  | 150         | 18                 | <b>550523</b>  | 6        |
| 5    | 150         | 24                 | <b>550525</b>  | 4        |
| 6    | 150         | 28                 | <b>550526</b>  | 4        |
| 7    | 200         | 40                 | <b>550527</b>  | 1        |

**Equipment included:** modular covers.  
**Features:** quick fitting with 1/4 turn screws.



**Click Cube front blind panels** at single height

| Size | Height (mm) | Palazzoli code | Pack Qty |
|------|-------------|----------------|----------|
| 2    | 125         | <b>550542</b>  | 6        |
| 3-4  | 150         | <b>550543</b>  | 6        |
| 5    | 150         | <b>550545</b>  | 4        |
| 6    | 150         | <b>550546</b>  | 4        |
| 7    | 200         | <b>550547</b>  | 1        |

**Features:** quick fitting with 1/4 turn screws.



**Click Cube front blind panels** at double height

| Size | Height (mm) | Palazzoli code | Pack Qty |
|------|-------------|----------------|----------|
| 2    | 250         | <b>550552</b>  | 4        |
| 3-4  | 300         | <b>550553</b>  | 4        |
| 5    | 300         | <b>550555</b>  | 1        |
| 6    | 300         | <b>550556</b>  | 1        |
| 7    | 400         | <b>550557</b>  | 1        |

**Features:** quick fitting with 1/4 turn screws.



**Click Cube reinforced DIN rails** for frames

| Size | No. of DIN modules | Palazzoli code | Pack Qty |
|------|--------------------|----------------|----------|
| 2    | 12                 | <b>550582</b>  | 6        |
| 3-4  | 18                 | <b>550583</b>  | 6        |
| 5    | 24                 | <b>550585</b>  | 1        |
| 6    | 28                 | <b>550586</b>  | 1        |
| 7    | 40                 | <b>550587</b>  | 1        |

**Equipment included:** complete with screws for mounting.



**Click Cube height-adjustable steel partial plates**

| Size | Height (mm) | Palazzoli code | Pack Qty |
|------|-------------|----------------|----------|
| 2    | 125         | <b>550632</b>  | 1        |
| 3-4  | 150         | <b>550633</b>  | 1        |
| 5    | 150         | <b>550635</b>  | 1        |
| 6    | 150         | <b>550636</b>  | 1        |
| 7    | 200         | <b>550637</b>  | 1        |

**Equipment included:** complete with screws for mounting.



Set of **brackets**  
for wall-mounting

| No. of brackets | Material         | Palazzoli code | Pack Qty |
|-----------------|------------------|----------------|----------|
| 4               | Galvanised steel | <b>550640</b>  | 20       |
| 4               | Stainless steel  | <b>550641</b>  | 5        |

**Features:** they can be mounted horizontally, vertically or hidden, retaining the double insulation.



**Distribution board kit**  
with frame windowed panels  
and DIN rails

| Size | No. of DIN modules | Palazzoli code | Pack Qty |
|------|--------------------|----------------|----------|
| 2    | 36 (3x12)          | <b>550042</b>  | 1        |
| 3    | 54 (3x18)          | <b>550043</b>  | 1        |
| 4    | 72 (4x18)          | <b>550044</b>  | 1        |
| 5    | 96 (4x24)          | <b>550045</b>  | 1        |
| 6    | 140 (5x28)         | <b>550046</b>  | 1        |
| 7    | 200 (5x40)         | <b>550047</b>  | 1        |



Pair of **accessories**  
for pole mounting

| Size  | Material | Palazzoli code | Pack Qty |
|-------|----------|----------------|----------|
| 1-2   | steel    | <b>550642</b>  | 1        |
| 3-4-5 | steel    | <b>550643</b>  | 1        |

**Features:** prearrangement for metal clamp for fastening to poles with diameter >80mm.



**Click Cube brackets**  
for fixing the cable ducts

| No. of brackets | Material | Palazzoli code | Pack Qty |
|-----------------|----------|----------------|----------|
| 8               | steel    | <b>550648</b>  | 1        |

**Equipment included:** complete with screws for mounting.

**Notes:** for all frame sizes. Suitable for cable ducts, max height 40mm.



**Click Cube adaptor kit**

| Size | Length (mm) | Palazzoli code | Pack Qty |
|------|-------------|----------------|----------|
| 2    | 70          | <b>550662</b>  | 1        |
| 3-4  | 110         | <b>550663</b>  | 1        |
| 5    | 150         | <b>550665</b>  | 1        |
| 6    | 190         | <b>550666</b>  | 1        |
| 7    | 240         | <b>550667</b>  | 1        |

**Notes:** the kit is used to install the Click Cube frame in boxes that were not made to accommodate it (before 2015).


The adaptors can also be used as spacers for the back plates.



**Security lock**  
with handle

| No. of keys | Material | Palazzoli code | Pack Qty |
|-------------|----------|----------------|----------|
| 2           | steel    | <b>550680</b>  | 10       |

**Features:** closing with Yale code key.



The background of the entire page is a deep blue space scene. At the top, the Palazzoli logo is displayed in white. Below it, the words 'excellence' and 'FROM ITALY' are shown, with 'excellence' flanked by green and red horizontal bars. The central part of the image features a bright sun or starburst on the horizon of the Earth, with numerous blue lines radiating outwards, connecting to a network of blue dots. The Earth's surface is visible, showing the outlines of continents and city lights. The overall theme is global connectivity and technological excellence.

# **Palazzoli**

— excellence —  
**FROM ITALY**

---

Palazzoli S.p.A  
25128 Brescia - Italy - Via F. Palazzoli, 31  
Tel +39 030 2015.1  
Fax +39 030 2015.258  
[www.palazzoli.com](http://www.palazzoli.com)  
[export@palazzoli.com](mailto:export@palazzoli.com)

---