

General Catalogue



2019/2020



CHIAREZZA DELLA FUNZIONE SEMPLICITÀ DI PROGETTO QUALITÀ DELLA MANIFATTURA

CLARITY OF FUNCTION PROJECT SIMPLICITY QUALITY OF MANUFACTURE

Palazzoli

355

Strait ST









TAIS

Excellent resistance to stresses, vibrations, abrasions and does not need any maintenance



thermosetting GRP, a fire retardant material that does not produce toxic gases and is resistant to installing in areas subject to possible flooding. chemicals over time.



All products of the TAIS series are made in Palazzoli The special gaskets in non-ageing elastomer guarantee a protection rating up to IP68, for



The back boxes are equipped with brass threaded Practically immune to the major part of all the inserts that ensure an easy opening and closing aggressive substances, they are the best solution of the cover even after long time.



for industrial installations under 1.5 m height.

Suitable for chemical industries, industrial facilities, plants with galvanic treatments, airports, cold rooms and in dusty, salty and corrosive atmosphere.



TAIS boxes represent the state of the art for industrial electrical junctions, both for wall-mounting or on machinery boards in insulating material. The offer is structured on two types of boxes, one is with small dimensions for mounting on board of machineries and the other is with medium and big dimensions to be wall-mounted for industrial plants.

Compliance with standards	IEC/EN 602208 IEC/EN 60670-1
Material	Palazzoli thermosetting GRP
Protection rating (IP according to IEC/EN 60529)	IP67 - IP68
Colour	RAL5015 (cover) RAL7042 (base)
Resistance to abnormal heat and fire ("Glow Wire" according to IEC/EN 60695-2-10)	960°C
Flammability rating (according to UL94)	VO
Impact resistance (IK rating according to IEC/EN 62262)	ікто
Insulation class	
Storage temperature	-50°C - +90°C
Operating temperature	-40°C - +90°C



Outer dimensions (mm)	Box height (mm)	Cover height (mm)	Palazzoli code	Pack Qty
92x92	50	18	538035	1
125x92	50	18	538045	1
185x92	50	18	538055	1
125x125	75	25	538116	1
185x125	75	25	538117	1
250x125	75	25	538118	1

Features: IP68 protection rating test is carried out at 2 m depth for 24 h. Blind walls.



Junction boxes in thermosetting GRP with high cover IP68

Outer dimensions (mm)	Box height (mm)	Cover height (mm)	Palazzoli code	Pack Qty
92x92	50	50	538005	1
125x92	50	50	538006	1
185x92	50	50	538015	1
125x125	75	50	538016	1
185x125	75	50	538017	1
250x125	75	50	538018	1

Features: IP68 protection rating test is carried out at 2 m depth for 24 h. Blind walls.

Technical accessories:







Junction boxes in thermosetting GRP with low cover IP67

Outer dimensions (mm)	Box height (mm)	Cover height (mm)	Palazzoli code	Pack Qty
92x92	50	18	532035	5
125x92	50	18	532045	1
185x92	50	18	532055	1
125x125	75	25	532116	1
185x125	75	25	532117	1
250x125	75	25	532118	1

Features: blind walls.



Back plates in galvanised steel for TAIS boxes

For box dimensions	For box code	Palazzoli code	Pack Qty
92x92	532005, 532035, 532225, 538005 538035, 532005, 532035	532705	1
125x92	532006, 532045, 532285, 532295 538006, 538045, 532006, 532045	532714	1
185x92	532015, 532055, 532325, 532385, 538015, 538055, 532015, 532055	532715	1
125x125	532016, 532116, 532346, 538016 538116, 532016EX, 532116EX	532716	1
185x125	532017, 532117, 532667, 532677, 538017 538117, 532017EX, 532117EX, 532667EX	532717	1
250x125	532018, 532118, 532618, 532628 532638, 532648, 538018, 538118 532018EX, 532118EX, 532628EX	532718	1

Uses: for fastening terminal blocks or non-modular devices.



Junction boxes in thermosetting GRP with high cover IP67

Outer dimensions (mm)	Box height (mm)	Cover height (mm)	Palazzoli code	Pack Qty
92x92	50	50	532005	1
125x92	50	50	532006	1
185x92	50	50	532015	1
125x125	75	50	532016	1
185x125	75	50	532017	1
250x125	75	50	532018	1

Features: blind walls.

Ie	cnnical acces	sories:	
	9	mindern	1144
	page 163	page 161	page 105



Boxes in thermosetting GRP with transparent cover IP67

Outer dimensions (mm)	No. of DIN modules	Power dissipation (W)	Palazzoli code	Pack Qty
125x125x125	4	13	532516	1
185x125x125	6.5	15	532557	1
250x125x125	9	20	532658	1

Features: blind walls supplied with drilling template. Padlockable cover and with tamper-proof screw.

Technical accessories:







TAIS Grande series distribution boxes are a range of products with thickened walls made of Palazzoli Thermosetting GRP for heavy duty applications with up to IP67 protection rating and resistant to UV rays. The system is composed of 5 sizes, complete with back plate made of zinc-tropicalised steel sheet, that can be accessorised with blind or transparent cover with moulded large captive screws with hexagonal insert of 8 mm. The boxes are available in versions totally blind or with windows on the sides that allow modular combinations.



Compliance with standards IEC/EN 602208 Material Palazzoli thermosetting GRP Protection rating (IP according to IEC/EN 60529) IP65 and IP67 Colour RAL5015 (cover) RAL7042 (base) Resistance to abnormal heat and fire (*Glow Wire" according to IEC/EN 60695-2-10) 960°C Flammability rating (according to UL94) Vo Impact resistance (IK grade according to IEC/EN 62262) IK10 Insulation class II II Storage temperature -50°C - +90°C Operating temperature -40°C - +90°C
Protection rating (IP according to IEC/EN 60529) IP65 and IP67 Colour RAL5015 (cover) RAL7042 (base) Resistance to abnormal heat and fire (°Glow Wire" according to IEC/EN 60695-2-10) 960°C Flammability rating (according to UL94) v0 Impact resistance (IK grade according to IEC/EN 62262) IK10 Insulation class II □ Storage temperature -50°C - +90°C Operating temperature -40°C - +90°C
(IP according to IEC/EN 60529) IP65 and IP67 Colour RAL5015 (cover) RAL7042 (base) Resistance to abnormal heat and fire (*Glow Wire" according to IEC/EN 60695-2-10) 960°C Flammability rating (according to UL94) V0 Impact resistance (IK grade according to IEC/EN 62262) IK10 Insulation class II □ Storage temperature -50°C - +90°C Operating temperature -40°C - +90°C
RAL7042 (base) Resistance to abnormal heat and fire (°Glow Wire" according to IEC/EN 60695-2-10) 960°C Flammability rating (according to UL94) V0 Impact resistance (IK grade according to UL94) IK10 Impact resistance (IK grade according to UL94) IK10 Insulation class II II Storage temperature -50°C - +90°C Operating temperature -40°C - +90°C
heat and fire ("Glow Wire" according to UEC/EN 60695-2-10) 960°C Flammability rating (according to UL94) V0 Impact resistance (IK grade according to UL94) IK10 Insulation class III □ Storage temperature -50°C - +90°C Operating temperature -40°C - +90°C
(according to UL94) vu Impact resistance (IK grade according to IEC/EN 62262) IK10 Insulation class II □ Storage temperature -50°C - +90°C Operating temperature -40°C - +90°C
(IK grade according to IEC/EN 62262) IK10 Insulation class II □ Storage temperature -50°C - +90°C Operating temperature -40°C - +90°C
Class III Storage temperature -50°C - +90°C Operating temperature -40°C - +90°C
temperature -50 C - +90 C Operating temperature -40°C - +90°C
COLOMBIA

Resistance to chemical agents									
			ACIDS BASES				SOLVENTS		
WATER SALINE SOLUTION		CONCENTRATED	DILUTED	CONCENTRATED	DILUTED	ALCOHOL	ACETONE	PERCHLORO- ETHYLENE	BENZENE
		\ominus	Î	\bigcirc	Î			1	1
OILS FATS									
MINERAL	VEGETABLE	ANIMAL	SYNTHETIC	AMMONIA	OXIDISERS	INORGANIC SALTS	GASOLINE	DETERGENTS	U.V. RAYS
1		\bigcirc	1		1	\bigcirc	1	1	1

Legend: ① high resistance 😔 partial resistance





Junction boxes in thermosetting GRP with back plate IP67

Outer dimensions (mm)	Window type	Installable TAIS socket module	Palazzoli code	Pack Qty
	blind walls	2x95	531011	1
	a→ a	2x95	531200	1
185x185x115	a t a	2x95	531211	1
		2x95	531311	1
-		-	531411	1
- 250X185X115 -	blind walls	2x95/2x125	531021	1
	ª→ T ← ª	2x95/2x125	531220	1
		2x95	531222	1
	t a b	2x95/2x125	531221	1
	Lightened ∞→↓↓← ∞ Lightened	-	531231	1
		2x95	531321	1
	a→[↓ b	2x95/2x125	531331	1
		-	531431	1

Outer dimensions (mm)	Window type	Installable TAIS socket module	Palazzoli code	Pack Qty
	blind wolls	2x95/2x125	531040	1
	Ď→	2x95/2x125	531241	1
250x250x115	Lightened b t Lightened	-	531240	1
200/200/110	b→ → ← b	2x95/2x125	531340	1
		-	531440	1
	Lightened	2x95/2x125	531540	1
	Lightened	2x95/2x125	531640	1
	Lightened ↓ Lightened	-	531042	1
370x250x115	Lightened b→t+ Lightened	-	531242	1
	b→+b a1a1	-	531442	1
	Lightened ↓ Lightened	-	531062	1
500x370x115	Lightened C→↓↓ Lightened	-	531262	1
		-	531662	1

Equipment included: free windows with gaskets in non-ageing elastomer. Screws and bolts for coupling or closing with flanges and back plate. Boxes up to 250x250 with drilling template. Features: they are used for making junction or distribution boards.

Boxes with dimensions 250 x 250 and larger are rated IP65.

Technical accessories:









Blind covers low in thermosetting GRP for TAIS Grande boxes **IP67**

For boxes with dimensions (mm)	Cover height (mm)	Palazzoli code	Pack Qty
185x185	25	535320	1
250x185	25	535321	1
250x250	25	535322	1
370x250	25	535323	1
500x370	25	535324	1

Equipment included: complete with captive screws that can be sealed. Features: covers with dimensions 250x250 and larger are IP65.



Blind covers high in thermosetting GRP for TAIS Grande boxes IP67

For boxes with dimensions (mm)	Cover height (mm)	Palazzoli code	Pack Qty
250x185	75	535325	1
250x250	75	535326	1
370x250	75	535327	1
500x370	75	535328	1

Equipment included: complete with captive screws that can be sealed. Features: the height of the cover allows to insert MCCB inside. Covers with dimensions 250x250 and larger are rated IP65.



Transparent covers low in polycarbonate for TAIS Grande boxes **IP67**

For boxes with dimensions (mm)	Cover height (mm)	Palazzoli code	Pack Qty
250x185	25	535126	1
250x250	25	535135	1
370x250	25	535137	1
500x370	25	535157	1

Equipment included: complete with captive screws that can be sealed. Features: in UV stabilised polycarbonate. Covers with dimensions 250x250 and larger are rated IP65.



Transparent covers high in polycarbonate for TAIS Grande boxes IP67

For boxes with dimensions (mm)	Cover height (mm)	Palazzoli code	Pack Qty
250x185	75	535131	1
250x250	75	535140	1
370x250	75	535142	1
500x370	75	535162	1

Equipment included: complete with captive screws that can be sealed. Features: in UV stabilised polycarbonate.

Covers with dimensions 250x250 and larger are rated IP65.



Windowed covers in polycarbonate for TAIS Grande boxes **IP67**

For boxes with dimensions (mm)	Cover height (mm)	No. of DIN modules	Palazzoli code	Pack Qty
185x185	80	7.5	535640	1
250x185	80	11	535643	1

Equipment included: complete with captive screws that can be sealed, DIN rail and small parts for fastening on a plate. Features: padlockable lid and with tamper-proof screw.

NOTES







Flat blind flanges in thermosetting GRP for windowed walls IP67

Туре	Window dimensions (mm)	Flange height (mm)	Palazzoli code	Pack Qty
a	110x60	15	538110	2
b	175x60	15	538210	2
С	295x60	15	538310	1

Uses: closing the cable entry windows. Holes can be drilled for applying cable glands.



Blind flanges raised in thermosetting GRP for windowed walls IP67

Туре	Window dimensions (mm)	Flange height (mm)	Palazzoli code	Pack Qty
a	110x60	45	538130	2
b	175x60	45	538230	2
С	295x60	45	538330	1

Uses: closing the cable entry windows. Holes can be drilled for applying cable glands. The increased height helps entry of large cables or pipes. They make wiring easier as they increase the internal volume of the enclosure.

Technical accessories:





Hinge frames with installation kit for TAIS Grande boxes

Description	Palazzoli code	Pack Qty
Single hinge in insulating material with screws, washers and gaskets	538385	1

Uses: with all TAIS series boxes in thermosetting GRP insulating material with screw cover (excluding those with 18 mm low cover). They cannot be fitted to walls with a window or near holes or knockouts.



Supports for bus bars for TAIS Grande boxes

Installable on windows	Installable bus bars (mm)	Palazzoli code	Pack Qty
a	3 x 16x4 (16x5 - 20x4 - 20x5), 2 by 16x4 (earth and neutral), 3 of ø 9 (auxiliary circuits)	538180	1
b	3 of 25x5 (25x6 - 32x5 - 32x6), 2 of 25x5 (earth and neutral), 3 of ø 11 (auxiliary circuits)	538280	1
С	6 of 40x5 (40x8 - 50x5 - 50x8), 4 of 25x5 (25x6 - 32x5 - 32x6)	538380	1

Uses: they are used to facilitate the application of conductor busbars in watertight distribution boards composed of equipment in TAIS Grande modular insulating boxes with windows type 'a', 'b' and "c".



Supports

for 90° angled wall-mounting of straight sockets and plugs **IP65**

Support base dimensions (mm)	Installable sockets/plugs	Box window	Palazzoli code	Pack Qty
142x113	63A	a	472967	1
142x113	125A	a	472968	1
207x113	63A	b	472977	1
207x113	125A	b	472978	1

Equipment included: 4 stainless steel screws for fixing the socket or the plug. Uses: for applications with combinable modular boxes in thermosetting GRP (with windows "a" or "b") or in aluminium (with windows F5).

Technical accessories:







excellence **FROM ITALY**

Palazzoli S.p.A 25128 Brescia - Italy - Via F. Palazzoli, 31 Tel +39 030 2015.1 Fax +39 030 2015.258 www.palazzoli.com export@palazzoli.com