

***Palazzoli***

**General**  
Catalogue



2019/2020

# ***Palazzoli***





CHIAREZZA DELLA FUNZIONE  
SEMPLICITÀ DI PROGETTO  
QUALITÀ DELLA MANIFATTURA

---

CLARITY OF FUNCTION  
PROJECT SIMPLICITY  
QUALITY OF MANUFACTURE



# CONTAINER



## Total protection

Thanks to resistance to salty atmosphere, UV rays and overtemperatures.



## AC3-AC23A

Thanks to the isolator switch at rated current.

Palazzoli - Via Palazzoli 31, 25128 Brescia Italy  
32A-3h/380V 50Hz-440V 60Hz  
50-60Hz X-CEE  
3P+G IP68/IP67/IP66/IP69  
770233  
Made in Italy



## Per container

Thanks to 380/440V, 3h, 32A plugs and sockets, the power supply of refrigerated containers is guaranteed.



Compliance with standards	<b>IEC/EN 60309-1 IEC/EN 60309-2 CEI EN 60309-4</b>
Protection rating (IP according to IEC/EN 60529)	<b>Thermosetting GRP page 96 Aluminium page 118 Thermoplastic material page 69 Technopolymer page 46</b>
Rated current	<b>32A 3P+<math>\neq</math> 3h</b>
Operating voltage	<b>380/440V</b>
Operating frequency	<b>50-60Hz</b>
Storage temperature	<b>Thermosetting GRP page 96 Aluminium page 118 Thermoplastic material page 69 Technopolymer page 46</b>
Operating temperature	<b>Thermosetting GRP page 96 Aluminium page 118 Thermoplastic material page 69 Technopolymer page 46</b>



Rated operating currentswitch:			32A
Thermal current Ith		A	32
AC21A	400V	A	32
AC22A	400V	A	32
AC23A	400V	A	32
AC23A	400V	kW	15
AC3	400V	kW	15

**THERMOSETTING GRP**

M32 ENTRY



**Interlocked socket-outlet**  
in thermosetting GRP  
with **MCB** for wall-mounting  
50-60Hz **IP67**

Rated current (A)	Rated voltage	Voltage colour	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	3P+ $\neq$	3	<b>474771</b>	1

M25 ENTRY



**Interlocked socket-outlet**  
in thermosetting GRP  
for wall-mounting  
50-60Hz **IP66/IP67**

Rated current (A)	Rated voltage	Voltage colour	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	3P+ $\neq$	3	<b>469233</b>	1

M32 ENTRY



**Interlocked socket-outlet**  
in thermosetting GRP  
for wall-mounting  
and **DIN rail**  
50-60Hz **IP67**

Rated current (A)	Rated voltage	Voltage colour	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	3P+ $\neq$	3	<b>472133</b>	1

Technical accessories:



page 163





**ALUMINIUM**

WINDOW F1



**Interlocked socket-outlet**  
in aluminium alloy  
with **MCB**  
for wall-mounting  
50-60Hz **IP67**

Rated current (A)	Rated voltage	Voltage colour	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	3P+≐	3	<b>474486</b>	1

WINDOW F1



**Interlocked socket-outlet**  
in aluminium alloy  
for wall-mounting  
50-60Hz **IP67**

Rated current (A)	Rated voltage	Voltage colour	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	3P+≐	3	<b>460233</b>	1

WINDOW F1



**Interlocked socket-outlet**  
in aluminium alloy  
with **DIN rail**  
for wall-mounting  
50-60Hz **IP67**

Rated current (A)	Rated voltage	Voltage colour	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	3P+≐	3	<b>472735</b>	1

Technical accessories:



page 158

**THERMOPLASTIC**



**Interlocked socket-outlet**  
for distribution boards  
50-60Hz **IP66/IP67**

Rated current (A)	Rated voltage	Voltage colour	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	3P+≐	3	<b>491233</b>	1

Technical accessories:



page 74



**15° angled**  
**flush-mounted fixed socket**  
50-60Hz **IP66/IP67**

Rated current (A)	Rated voltage	Voltage colour	Dimensions (mm)	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	88x100	3P+≐	3	<b>489233</b>	1

Technical accessories:



page 35

page 35



**TECHNOPOLYMER**



**Straight panel-mounted socket**  
50-60Hz  
**IP66/IP67/IP68/IP69**

Rated current (A)	Rated voltage	Voltage colour	Dimensions (mm)	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	65x83	3P+≐	3	<b>772233</b>	1

Technical accessories:



page 91



**Coupler**  
50-60Hz  
**IP66/IP67/IP68/IP69**

Rated current (A)	Rated voltage	Voltage colour	Dimensions (mm)	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	88x100	3P+≐	3	<b>770233</b>	1



**Straight panel-mounted rotoswitched socket**  
50-60Hz  
**IP66/IP67/IP69**

Rated current (A)	Rated voltage	Voltage colour	Dimensions (mm)	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	65x83	3P+≐	3	<b>412233</b>	1

Technical accessories:



page 91


page 91



**Plug**  
50-60Hz  
**IP66/IP67/IP68/IP69**

Rated current (A)	Rated voltage	Voltage colour	Poles	h ref.	Palazzoli code	Pack Qty
32	380/440V	●	3P+≐	3	<b>760233</b>	1

Technical accessories:



page 47

The background of the entire page is a night-time satellite view of the Earth, showing the illuminated landmasses of Europe and Africa. A bright sun or star is positioned at the horizon, creating a lens flare effect. Overlaid on this image is a network of glowing blue lines connecting various points, resembling a global communication or data network. The Palazzoli logo is prominently displayed at the top center.

# **Palazzoli**

— excellence —  
**FROM ITALY**

---

Palazzoli S.p.A  
25128 Brescia - Italy - Via F. Palazzoli, 31  
Tel +39 030 2015.1  
Fax +39 030 2015.258  
[www.palazzoli.com](http://www.palazzoli.com)  
[export@palazzoli.com](mailto:export@palazzoli.com)

---