## HYDRAULIC CUTTING TOOL

## HT-TC026Y

overhead line application

## MAIN APPLICATIONS

specifically designed to cut Copper, aldrey, Aluminum, Aluminum-Steel cables, stay wire and Steel ropes having Ø max 25 mm and Steel earthing rod up to 16 mm.

394,5

129

3,35

STORAGE		TECHNICAL FEATURES
Туре	CVB-001	Max cutting Ø mm
Dimensions mm L x W	430 x 155	Dimensions mm
Weight kg	0,15	Length
Supplied with the tool	√	Width
Purchase separately	-	Weight kg



Hand operated hydraulic tool specifically designed to cut Copper, aldrey, Aluminum, Aluminum-Steel cables, stay wire and Steel ropes having a max overall diameter of 25 mm and Steel earthing rod up to 16 mm. The tool features a double speed action.

The blades are manufactured from high strength special Steel, heat treated to ensure a long service life.

> The head can rotate through 180 degrees, to enable the operator to work in the most comfortable position, and can easily be opened to allow the cutting of running cables. HT-TC026Y features an automatic safety valve to bypass oil when reaching maximum pressure; a pressure release device can also be operated at any stage of operation.

ldeal for earthing rod and stay wire

HT-TCO26Y cutting capa	city - a few examples:		
Ø			
mm	in.		
14,2	/	STEEL EARTHING ROD, COPPER PLATED; Tensile strength = 79 daN/mm <sup>2</sup>	
12,7	1/2″	STEEL EARTHING ROD, COPPER PLATED; Tensile strength = 69 daN/mm <sup>2</sup>	
15,6	/	STEEL EARTHING ROD; Tensile strength = 69 daN/mm <sup>2</sup>	
15,9	5/8″	STEEL EARTHING ROD, COPPER PLATED (CON ED - ILLINOIS); Tensile strength = 57 daN/mm <sup>2</sup>	
15,9	5/8»	STEEL EARTHING ROD, COPPER PLATED (CON ED - STATEN ISLAND); Tensile strength = 78 daN/mm <sup>2</sup>	
19	3/4″	STEEL EARTHING ROD, COPPER PLATED; Tensile strength = 74 daN/mm <sup>2</sup>	
9,15 (3,05x7)	/	STAY WIRE	
10,8 (3,6x7)	/	STAY WIRE (PORTLAND GENERAL ELECTRIC)	
11,1 (3,7x7)	/	STAY WIRE (PORTLAND GENERAL ELECTRIC)	
12,3 (4,1x7)	/	STAY WIRE (PORTLAND GENERAL ELECTRIC)	
12,6 (4,2x7)	/	STAY WIRE (PORTLAND GENERAL ELECTRIC)	