

# KTS1632

## HAND TOOLS

for cutting and sealing flexible plastic conduit



Cuts and seals flexible plastic conduit in a single operation. Lightweight and easy to operate. Suitable for flexible conduits from Ø16 to Ø32 mm.

### TECHNICAL FEATURES

#### Dimensions mm

Length	230
Width	58
Thickness	32
Weight kg	0,32

# PC1

for cutting plastic pipe



Plastic pipe cutting tool  
Cutting capacity: Ø 6 to Ø 42 mm.

Body: die-cast aluminium alloy  
Blade material: hardened Carbon Steel

### TECHNICAL FEATURES

#### Dimensions mm

Length	195
Width	96
Thickness	27
Weight kg	0,32

# MT-FC48N

## FRAME-TYPE HOLE PUNCHING TOOL

for cable trunking



Lightweight and easy to operate, designed for punching holes up to 47,2 mm diameter in the side wall of trunking without the need for pre drilling.



**VAL-P30**  
Supplied in a robust plastic case.

Table denotes the punch/die set reference, for each hole size. Suitable for punching holes in mild steel, fibreglass or plastic material, up to 2 mm thick.

Hole Dimensions					Maximum thickness of mild steel (mm)	Type
Nominal						
Ø (mm)	Ø (inch)	Pg	ISO	Inch		
15,5	.610	Pg9	-	-	2	RD15.5SS-FC
16,2	.638	-	ISO-16	-		RD16.2SS-FC
17,5	.689	-	-	-		RD17.5SS-FC
18,8	.740	Pg11	-	-		RD18.8SS-FC
19,1	.752	-	-	-		RD19.1SS
20,5	.807	Pg 13,5	ISO-20	-		RD20.5SS
22,6	.890	Pg16	-	-		RD22.6SS
23,8	.937	-	-	5/8"		RD23.8SS
25,4	1.000	-	ISO-25	-		RD25.4SS
27,0	1.063	-	-	3/4"		RD27.0SS
28,5	1.122	Pg21	-	-		RD28.5SS
30,5	1.201	-	-	7/8"		RD30.5SS
31,8	1.252	-	-	-		RD31.8SS
32,5	1.279	-	ISO-32	-		RD32.5SS
34,6	1.362	-	-	-		RD34.6SS
37,2	1.464	Pg29	-	-		RD37.2SS
38,1	1.500	-	-	-		RD38.1SS
40,5	1.594	-	ISO-40	-		RD40.5SS-FC
41,3	1.626	-	-	-		RD41.3SS-FC
42,5	1.673	-	-	1 1/4"		RD42.5SS-FC
43,2	1.701	-	-	-		RD43.2SS-FC
44,5	1.752	-	-	-		RD44.5SS-FC
47,2	1.858	Pg36	-	-		RD47.2SS-FC