



# EV Charger

## AC-EVC-010 Stand Alone

The FIMER AC EV Charger line is based on solidity and functionality, in compliance with the international IEC 61851-1 standard.

AC-EVC-010 Stand Alone is a 2x22kW island mode charging point able to provide the maximum power required by the vehicle, according to the recharge, protection and network conditions.

**2x22 kW**

Two Type 2 sockets, equipped with all the measurement and protection systems, electromechanical retention during charging, communication with the electric vehicle, connection monitoring and regulation of the current through PWM and differential protection circuit breaker type B.

- Color-coded Status LED for each socket (Ready to use, Charging, Alarm, etc ...)
- Smart fault management, with automatic reclosure of the circuit breaker.
- Internal load manager for the distribution of the maximum load set by the user, between the two sockets.
- Plug & Charge operation mode.
- Back-up power supply with super "Supercap" capacitors.
- Internal temperature sensors.
- Stainless steel case.

- Charging sockets equipped with protection and safety systems.
- Automatic re-close differential breaker
- Shutter-type auto reclosing sockets, vandal-proof

#### Signaling and control

- Status LEDs and light signaling

#### Types of connectors

- Connector type 2
- IEC/EN 62196-2
- Station fixed socket
- Connector used for AC recharging up to 22 kW



2x22 kW

### Technical data

Model	AC-EVC-010			
Charging mode / Case	Mode 3, case B <sup>1)</sup>			
Type of sockets	Type 2 <sup>2)</sup>			
Maximum AC power	2x22 kW			
Operating voltage	3x 400V <sub>AC</sub> +/-10% (50 o 60 Hz)			
Maximum current deliverable	32A			
IP protection class	IP 54			
Casing material	Stainless steel AISI 304			
IK protection class (external impacts)	IK10			
Dimensions	1315x437x293			
Weight	48 Kg			
Enviroment data				
Operating temperature	-25°C ... 50°C			
Storage temperatures	-25°C ... 70°C			
Humidity	0 % ... 95 % (without condensation)			
Altitude	Up to 2000m			
Type of installation	Suitable also for outdoor installation			
Internal components				
Circuit breaker protection switch	4X D40			
Leakage detect protection	According to IEC 61851, made by RCM (RCD Type B optional)			
Energy Meter	MID certified 3ph + N	3x400/230V kWh Class B <sup>3)</sup>	kWh Class 1 <sup>4)</sup> kVar Class 2 <sup>5)</sup>	RS485 monitor
Contactor	4xNO 40A, AC-1 @40°C Aux Contact 1xNO + 1xNC			
Plug-socket	PWM-CP, PP <sup>1)</sup>			
Electronic control board				
Board power supply voltage	24 V <sub>DC</sub> ±5%			
Internal diagnostic systems	Measurement of all internal tensions	Monitoring of internal temperatures	Monitoring of the status of the contactor and of the circuit-breaker	Ground fault reclosure system Monitoring of electromechanical component states
Electronic control board	Microprocessor			

1) According to IEC 61851-1.

2) According to IEC 62196-2.

3) According to EN50470-3.

4) According to EN62053-21.

5) According to EN62053-23.

**Remark. Features not specifically listed in the present data sheet are not included in the product**



For more information  
please contact  
your local FIMER  
representative or visit:

fimer.com

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. FIMER does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of FIMER. Copyright© 2020 FIMER. All rights reserved.

