



This range of terminals features contained palm width and has been specifically developed for application on L.V. circuit breakers with reduced space terminal blocks.

The contained palm width allows an immediate and easier installation.

Cembre terminals are manufactured from electrolytic Copper tube.

The specifically designed section of the barrel and the choice of principal dimensions are optimising the best combination of mechanical strength and electrical conductivity.

These terminals are annealed to guarantee optimum ductility and are electrolytically Tin plated to avoid oxidation.

Cond. Size Flexible sqmm	Ø Stud mm	Type	Dimensions mm						Quantity Box/Bag	Mechanical Tools			Hydraulic Tools				
			ØI	B	M	N	L	d		HN5	HN-A25	TN70SE	B15MD	HT45-E	HT51	B500ND	RHU81
10	5	A2-M5/9	4,6	9,0	6,5	6,0	26,0	5,3	1.000/100								
16	5	A3-M5/9	5,8	9,0	6,5	6,0	29,0	5,3	1.000/100								
25	5	A5-M5/9	7,0	9,0	6,5	6,0	31,5	5,3	500/100								
35	6	A7B-M6/11.5*	8,9	11,5	8,0	7,0	36,5	6,4	400/100								
50	6	A10B-M6/11.5*	10,0	11,5	8,0	7,0	40,5	6,4	200/50								
70	6	A14B-M6/11.5*	11,3	11,5	8,0	7,0	44,0	6,4	200/50								
95	8	A19B-M8/15.5*	13,5	15,5	9,0	8,0	52,5	8,4	100/25								
120	8	A24B-M8/19*	15,2	19,0	14,0	9,0	60,0	8,4	100/25								
	10	A24B-M10/19*	15,2	19,0	14,0	9,0	60,0	10,5	100/25								
150	8	A30B-M8/19*	16,7	19,0	18,0	9,0	70,0	8,4	50/25								
	10	A30B-M10/19*	16,7	19,0	18,0	9,0	70,0	10,5	50/25								
185	10	A37B-M10/24.5*	19,2	24,5	18,0	9,0	77,0	10,5	50/25								
240	10	A48-M10/31	21,1	31,0	13,0	9,0	80,0	10,5	30/15								
	12	A48-M12/31	21,1	31,0	16,0	12,0	86,0	13,2	30/15								
	16	A48-M16/31	21,1	31,0	19,0	17,0	94,0	17,0	30/15								
300	10	A60B-M10/31	23,7	31,0	16,0	12,0	95,0	10,5	20/10								
	12	A60B-M12/31	23,7	31,0	16,0	12,0	95,0	13,2	20/10								

*Without inspection hole

The barrel is provided with an internal taper to ease the introduction of the conductor; furthermore, its length grants a comfortable and correct positioning between dies, during crimping operations.

Each palm is marked with the Cembre logo and part number.

Details of the appropriate crimping tools and dies are shown on pages 230 to 231.

