



DI, DC 24 V, 3-wire

DI 3x DC 24 V, 3-wire

- 24 V DC input voltage
- Can accommodate 3-wire sensors
- Fuse for 24 V DC
- A blue LED indicates the module's operating status
- Green LEDs (one for each input) indicate the input status
- 3 inputs, electrically isolated from the backplane bus

Technical specifications

General information	
Order number	600-210-0CC01
Article name	DI 3 x DC 24 V, 3-wire
Scope of delivery	DI 3 x DC 24 V
Dimensions (DxWxH)	110 x 14 x 73 mm
Weight	Approx. 70 g
Number of inputs	3
Electrical isolation	
from the backplane bus	Yes
Between the channels	No
Current draw	
External	Max. 0 mA
Internal	Max. 22 mA
Power dissipation	Max. 0.7 W
Input characteristic curve	Type 2, EN 61131-2
Reverse polarity protection for inputs	Yes
Input voltage	
For signal "0"	-3 V ... 9 V
For signal "1"	12 V ... 30 V
L+ fuse	4 A
Hot-swap capable	Yes
Ambient conditions	
Ambient temperature	0 °C ... +60 °C
Transport and storage temperature	-20 °C ... +80 °C
Relative air humidity	95 % r H without condensation
Protection rating	IP 20

Certifications	CE, UL
UL	
Surrounding Air Temperature	0 °C ... +60°C
Pollution degree	2
CE	
Noise immunity	DIN EN 61000-6-2 "EMC Immunity"
Interference emission	DIN EN 61000-6-4 "EMC Emission"
Vibration and shock resistance	DIN EN 60068-2-6:2008 „Vibration“, DIN EN 60068-2-27:2010 „Shock"
RoHS	Yes
REACH	Yes