MECHANICAL TOOLS CRIMPST	AR [®] RANGE HN-A25
for uninsulated terminals and connectors A-M,	L-M and L-P series
Crimpstar	Cempstari 6 00
for Cu tube lugs DR (DIN 46235) and through comm	ectors D SV (DIN 46267) HN-D25
Crimpstar'	
Example	Combra Co Office Grimpstan Go Office
for Cu tube lugs HR and through conne	ectors HSV HN-H25
Crimpstar Image: Complexity of the second	Crimpatari O O O O O O O O O O O O O O O O O O O
Crimpstar [®]	Crimester? 0 0 0 0000
HN-A25 TECHNICAL FEATURES:	
Crimping Range Uninsulated terminals and connectors A-M, L-M and L-P series for conductor sizes 10 to 25 sqmm	
HN-D25 TECHNICAL FEATURES: Cu tube lugs DR (DIN 46235) and through connectors DSV (DIN 46267)	RELEASE BALANCED DURABLE
Cultude lugs DK (Dirk 46235) and through connectors D5V (Dirk 46267) for conductor sizes 10 to 25 sqmm	HEXAGONAL
HN-H25 TECHNICAL FEATURES:	
Cu tube lugs HR and through connectors HSV for conductor sizes 10 to 25 sqmm	Dimensions mm Length 229
HN-T25 TECHNICAL FEATURES:	Width 78,6 Height 18,3
Crimping Range Cu tube lugs T-M, T-L and through connectors L-T for conductor sizes 10 to 25 sqmm	Weight g500Package Dimensions240 x 81 x 25