

## HYDRAULIC CUTTING TOOL

overhead line application

### MAIN APPLICATIONS

specifically designed to cut Copper, Aluminum, Aluminum-Steel cables (ACSR) having Ø max 50 mm  
Not suitable for cutting stay wire, Steel rope or earthing rod

### STORAGE

|                        |           |
|------------------------|-----------|
| Type                   | CVB-010   |
| Dimensions mm L x W    | 545 x 160 |
| Weight kg              | 0,15      |
| Supplied with the tool | ✓         |
| Purchase separately    | -         |

### TECHNICAL FEATURES

|                  |     |
|------------------|-----|
| Max cutting Ø mm | 50  |
| Dimensions mm    |     |
| Length           | 503 |
| Width            | 129 |
| Weight kg        | 4,7 |

Hand operated hydraulic tool specifically designed to cut Copper, Aluminum, Aluminum-Steel cables (ACSR) having a max overall diameter of 50 mm.

The HT-TC051Y is provided with a two stage hydraulic system, which advances the blades quickly to the cable. This proven system saves operator time and effort.



The HT-TC051Y is provided with an automatic safety valve to bypass oil when reaching max pressure. This means safety to the operator and protection to the blades. The blades are manufactured from high strength special Steel, heat treated to ensure a long service life. The shape of the blades provides a "clean" cut. The head can be opened to allow cutting of running cables and ropes. The head rotates 90 degrees allowing the operator to perform the cut in the most comfortable position. The tool is supplied complete with canvas bag 010 for protection and storage when not in use.

## HYDRAULIC CUTTING HEAD

overhead line application

### MAIN APPLICATIONS

specifically designed to cut Copper, Aluminum, Aluminum-Steel cables (ACSR) having Ø max 50 mm  
Not suitable for cutting stay wire, Steel rope or earthing rod

### STORAGE

|                         |           |
|-------------------------|-----------|
| Type                    | CVB-011   |
| Dimensions mm L x W x H | 360 x 137 |
| Weight kg               | 0,13      |
| Supplied with the tool  | ✓         |
| Purchase separately     | -         |

### TECHNICAL FEATURES

|                            |     |
|----------------------------|-----|
| Max cutting Ø mm           | 50  |
| Max operating pressure bar | 700 |
| Dimensions mm              |     |
| Length                     | 331 |
| Width                      | 112 |
| Weight kg                  | 3,3 |

Hydraulic cutting head complete with quick automatic coupler for connection to a hydraulic pump with a working pressure of 700 bar max, (see page 202-208).



TC050Y features the same cutting capability as HT-TC051Y.