



Building Automation

Solutions for Home Automation

Home Automation

Solutions for



Lighting control

Climate control

Blind and awning control

Alarms

Energy savings

ABOUT CARLO GAVAZZI

Carlo Gavazzi Automation is a multinational electronics group active in the design, manufacture and marketing of electronic equipment targeted at the global markets of industrial and building automation.

Our history is full of firsts and our products are installed in a huge number of applications all over the world. With more than 80 years of successful operation, our experience is unparalleled.

We have our headquarters in Europe and numerous offices around the world. Our R&D competence centres and production sites are located in Denmark,

Italy, Lithuania, Malta and the People's Republic of China.

We operate worldwide through 22 our own sales companies and also selected representatives in more than 65 countries, from the United States in the West to the Pacific Rim in the East.

Our core competence in automation spans four product lines: Sensors, Switches, Controls and Fieldbuses.

Our wide array of products includes sensors, monitoring relays, timers, solid-state relays, electronic motor controllers, energy management equipment and fieldbus systems.

We focus our expertise on offering state-of-the-art product solutions in selected market segments.

Our customers include original equipment manufacturers of packaging machines, plastic-injection moulding machines, food and beverage production machines, conveying and materials handling equipment, door and entrance control systems, lifts and escalators, as well as heating, ventilation and air-conditioning devices.

Our offer for the Home Automation consists of innovative solutions, designed to make a comfortable living environment, according to your mood and requirements as well as weather conditions.

Comfort, Security, Control, Flexibility and Ease are the synthesis of our commitment for an "intelligent" Home Automation system.



DESIGNED TO MEET MARKET REQUIREMENTS

The new home automation system by Carlo Gavazzi is the evolution of the well-known smart-house system: it looks after your houses in the best possible way, making them comfortable for you and your loved ones. It combines this comfortable living with energy saving, using state-of-the-art technology to improve your well-being and to reduce your carbon footprint.

The complete range of products is designed in Italy.

The system is based on a centralised structure, where the controller is the “brain” that supervises all the domestic functions such as lights, temperatures, rollerblinds, shutters and intruder, gas

and water leaks alarms.

New modules and functionalities can be added at any time, making the home “alive” and letting you adapt it according to your wishes, which might change over time.

It also allows you to be aware of energy consumption, providing diagrams of current consumption as well as the logging of what has been consumed in the previous days, months or years. All this data is easily accessible using smart-phones, PCs or tablet PCs. Retrofit installations can also be made when using this new Carlo Gavazzi system, as it features a full range of wireless products that can be used when wiring is not possible or not desired.

The new web server complements traditional methods of managing

sophisticated home automation technologies. It is embedded into the SH2WEB controller and it is completely configurable so that you can select your own themes.

The webserver is also designed as webapp to be accessible via any smart-phone, tablet pc.

The intuitive, user-friendly interface allows the control of lights, rollerblinds, alarms, timers, temperatures and more, both remotely and on site, all from a multi-function device.

Furthermore, the webserver/webapp enable access to the datalogger where energy data, temperatures and other events are stored, in order to have a clear overview of which appliances are on and how much they are consuming.

Home Automation

Bus intelligence made by experience



Sequences



Scheduler and Real time clock



Simulated habitation



Up&Down control and Shadowing




Heating and Cooling control



Fan control

Bus and power in the same cable

The bus and power wires follow the same logical path. The "switch wires" needed in conventional installations can be eliminated by use of de-central relays. The installation is fast and simple and last-minute changes are easily accommodated. No special cable or cable termination is required for the bus.



Fast commissioning with no addressing

One of the most innovative features of this system is that no addressing of modules is needed. The installer only has to mount all the components, launch a network scan and the system will automatically find and recognize the connected devices, making the correct association or addressing. This will result in time and cost savings, besides providing an error-free configuration process.



Energy efficient light management



Scenarios and Light control



Data logging and Event logging



Intruder alarm



Smoke alarm



Water leakage alarm

Diagnostic function

Immediate trouble-shooting is assured as the system monitors all the connected devices and advises if one is faulty. The load of the bus is constantly monitored and any anomaly is at once detected and reported.

All the information about short-circuits, bus voltage and load, noise level and quality of the bus signals is logged in a file both locally and remotely accessible.

This can be checked anytime, providing effective time and money savings.



Easy configuration software

The system configuration can be easily done by means of its wizard tools.


The user-friendly interface of this software guides the user in the creation of the pre-defined functions.

At the same time, thanks to many basic functions, the most skilled user can also create customized applications.

Test modes are getting easier by the several debug features available.

Home Automation

Lighting control



Glass touch switches

SHG060WLS4
SHG060BLS4
SHG503WLS6
SHG503BLS6

Glass touch switches for dimming control

SHG503BSLD
SHG060WSLD
SHG503WSLD
SHG060BSLD

Light switches

SHA4XWLS4
SHE5XWLS4
SHA4XLS4TH
SHE5XLS4TH

PIR detectors and lux meters

SHE5XP150L
SHA4XP150L

Dimmer modules

SH2D500WE230
SH2D10V424

I/O modules

SH2RE16A4
SH2RE16A2E230
SHDWRE16E230

Carlo Gavazzi offers integrated lighting automation and control. Lighting sets the perfect scene and creates the desired ambience for any occasion. Whether it is a movie night, an intimate dinner for two or a party with friends, lighting establishes the right mood.

The lights can create pre-programmed scenes to simulate the chosen lifestyle patterns. Dimmers do not just set the right atmosphere and create specific entertainment options, they can save money too. Most of the time we do not need to set our lights to full brightness to light a room, and if you dim your lights you are using less energy to run them. This is the aim of the new dimming technology by Carlo Gavazzi,

in addition to the integration of brand new energy-saving alternatives such as LED lamps.

The garden lights can be turned on by a light level sensor, whereas the entrance lights can be activated by a movement sensor.

Occupancy sensing, which turns off

lights when they are not needed, makes Carlo Gavazzi solutions ideal also for special applications such as light management in corridors and staircases.

Comfort and energy saving at a single touch are assured, without sacrificing style or convenience.



Climate control



Glass touch switches for temperature

SHG503BSLT
SHG060WSLT
SHG503WSLT
SHG060BSLT

Temperature controls

SHA4XTEMDIS
SHE5XTEMDIS
SHA4XLS4TH
SHE5XLS4TH

Outdoor temperature sensors

BSI-TEMANA-U
BSI-TEMANAB-U

Environmental sensors

SHSUXXXXD
SHSUXXXXL
SHSUXXXX

Analogue I/O

SHPINV2T1P124
SHPOUTV224

Relay modules

SH2SSTRI424
BDA-RE13A-U
SH2RE16A2E230

Carlo Gavazzi maintains your home at a comfortable level at all times, monitoring temperature and humidity levels automatically.

There is no need to get up or even be at home to adjust the temperature: with our Home Automation range of products you can control multiple

zones from one location and easily pre-set temperature set points.

You can keep your home at a more energy efficient temperature while you are out and programme it to automatically adjust to more comfortable levels by the time you get home.


Coming home early? Use your mobile phone or PC to control the climate remotely, even monitoring the wine cellar or greenhouse temperature and humidity level.

The Home Automation system by Carlo Gavazzi also helps you to save energy and money: demand-based energy use can be achieved via a timer program with a temperature profile or even via a presence signal. As the temperature variables of all the rooms are available centrally via the bus system, heating and cooling energy can be generated according to demand and with a high level of efficiency.



Home Automation

Blind and awning control



**Light switches,
PIR and lux meter**

**SHA4XLS4P90L
SHE5XLS4P90L**

Anemometer

BSN-ANE-U

**Lux
meter**

BSH-LUX-U

**DC up&down
module**

SH2RODC224

**AC up&down
modules**

**SH2ROAC224
SHDRODC230**

The installation of intelligent control technology in houses allows for the flexible control of blinds and shutters. In this way you can select various control options as:

- Classic control with conventional buttons and switches
- Control from remote PCs and smartphones
- Connection of multiple blinds/shutters to groups
- Realization of central functions such as "all up" buttons, "all blinds on the south side up" or similar


Thanks to full flexibility, it is possible to change switch assignment. Shutter-groups can be created at any time through our configuration software.

Furthermore, automation can be specified to respond to a number of different factors:

- Solar control, where the device operates automatically when a certain intensity of light is received by the sensor.
- Timers may be specified.
- An anemometer (wind speed sensor) is fitted so that the blind is retracted in windy conditions.
- Rain sensors may be used in order not to wet the blinds or dirty the window glass.



Alarms



Presence detectors

**SHSQP360L
BSx-PIR90-U
BxX-PIR90-U**

Smoke detectors

**BSG-SMO-U
BSG-SMOA-U**

Water detector

BSF-WAT-U

Wireless window sensors

**SHDWWISEN
SHDWWISENIN1**

Programmable keypad

BACC-KEYPAD-DC-U

Carlo Gavazzi protects your home. A water leakage in your kitchen or laundry room can be immediately detected by a sensor at floor level and the water supply will be interrupted, preventing loss and damage. At the same time an SMS message will promptly inform you when you are away from home.

Smoke detectors at different locations in your house are the main elements in the fire alarm system, and can be combined with other functions, for example lights can be switched on and fans switched off in case of fire.

The intruder alarms can be programmed so that house lights flash when there is a security breach, as well as sounding

the siren. Switching lights on and off in each room at two-second intervals is psychologically distracting and makes it extremely difficult for an intruder to search for jewellery and information such as credit card details. It also draws attention to the house from outside, further deterring any intruder



from their actions. The system can also play back loud music or alarm sounds in each room, to further persuade the intruder to leave. Naturally, the police can be notified automatically, along with key-holders and other designated people.



Home Automation

Energy saving



**Relay module
with
energy reading**

SH2RE16A2E230

**Wireless relay
with
energy reading**

SHDWRE16AE230

**Dimmer module
with
energy reading**

SH2D500WE230

**Pulse
counter**

SH2INDI424

**Energy
meters**

**EM33
EM21 - EM23
EM24 - EM26**

Incorporating a home automation system into a new or existing structure makes it easier to reduce energy consumption, also in combination with energy efficient lighting, Energy Star appliances and alternative energy sources.

Another effortless way to enhance the energy efficiency in your home is to take control of your energy consumption, by finding out exactly how much you are using.

Many electricity companies offer lower rates during off-peak hours, such as evenings and weekends. Using appliances such as washing machines, dryers, air conditioners and dishwashers during these hours can

lead to substantial savings on your electricity bill.

These real-time energy usage measurements will lead you to become more efficient with your energy consumption needs and will result in significant energy savings.

The system reads and logs the energy consumption of the whole installation or of a single load.

Data can be accessed anytime by means of a webserver/webapp and shown as instantaneous values, or in the form of graphs and/or diagrams.



Scenarios



Touch screen 4"

Touch screen 7"

BTM-T4-24

BTM-T7-24

Entertainment scenario

- TV and Home Theatre
- Music Surround
- Lights
- Heating or Air Conditioning
- Roller Blinds

Holidays scenario

- Heating
- Alarms
- Roller Blinds
- Doors and Windows
- Automatic Irrigation
- Automatic turn on/off of lights


Night & Day scenario

- Roller Blinds & Awnings
- Exterior Lighting
- Heating or Air Conditioning
- Automatic Irrigation (at the set time)



Home Automation

The controller



Controller

Wired bus generator

Wireless bus generator

DALI bus generator

Universal mobile modem

Digital input module

SH2WEB24

SH2MCG24

SH2WBU230

SB2DALI230

SH2UMMF124

SH2D10V424

The Carlo Gavazzi smart-house system is based on a central CPU, the SH2WEB24, a Linux based embedded PC that manages all the smart functions.

It is programmed by means of powerful software, the SH tool.

The SH2WEB24 has Ethernet communication capability in order to be remotely controlled and monitored by smart-devices/PCs. It also acts as a datalogger, which can record any kind of value/event coming from the many buses it can be connected to (Wireless and Dupline buses, two RS485 ports).

The master unit is also provided with an sd-card and USB port, which allow data uploading/downloading and system configurations.

Where wired Internet access is not available, Carlo Gavazzi provides a specific mobile modem to be added to the SH2WEB24.

This modem makes it possible to control any remote installation, whether it be a cabin in the mountains or a house at the seaside.


If the SH2WEB24 can be considered the "brain" of the smart-house system, the two bus generators are the pulsating "heart" that makes all the information flow.

They are connected to the SH2WEB24 via the high speed bus that is present both on the local bus and on the terminals at the bottom.

This means that the connection is very fast and easy in a cabinet, since the modules just have to be plugged together without any wiring.

At the same time it is very straightforward if the bus generators have to be mounted in different cabinets.

Up to 7 bus generators can be connected to one SH2WEB24.



Solid state relay output module

SH2SSTRI424

Relay modules

SH2RE16A4
SH2RE1A424

Relay module with energy reading

SH2RE16A2E230

Up/down modules for AC/DC motors

SH2ROAC224
SH2RODC224

Dimmer module with energy reading

SH2D500WE230

1-10 V Dimmer module

SH2D10V424

SH2MCG24 - the wired bus generator of smart Dupline®

The SH2MCG24 module is the smart Dupline bus generator, which provides the dupline bus on the local bus and on the terminals at the top.

Thanks to this, the DIN-rail slave modules (dimmers, relays, rollerblind modules, etc...) can simply be plugged into the SH2MCG24, without the need for any wiring.

The decentral modules, such as light switches, PIR sensors and temperature display, are connected to the SH2MCG24 with the two wires coming out from the terminals at the top.

SH2WBU230 - the wireless bus generator of WiDup

The smart-house system also provides a solution where it is not possible to use existing wiring, especially during the renovation of buildings.

The SH2WBU230 is the wireless bus generator that can control wireless light

switches and output relay modules. The wireless bus is based on the standard IEEE 802.15.4 @2.4Ghz.

Up to 250 modules can be managed by one SH2WBU230.

The open-space operating distance is 100 metres.



Home Automation

Our product range

Controller



SH2WEB24

- Master unit: home automation functions and energy data logging configurable by software
- Two RS485 communication ports (Modbus)
- One Ethernet port
- Two multi purpose USB 2.0 ports
- Micro SD

MAIN FEATURES

- Dimensions: 2-DIN modules
- DC power supply

Wired bus generator



SH2MCG24

- Connection to SH2WEB24 via internal bus or terminals via the high speed bus
- Up to 7 SH2MCG24 can be connected on the same network, considering the sum of SH2MCG24 and SH2WBU24

MAIN FEATURES

- Dimensions: 2-DIN modules
- DC power supply

Wireless bus generator



SH2WBU230

- Wireless transmission based on IEEE 802.15.4, @ 2.4 GHz
- Maximum slave number: 250
- Up to 4 SH2WBU230 can be connected on the same network
- Connection to SH2WEB24 via internal bus or terminals via the high speed bus

MAIN FEATURES

- Dimensions: 2-DIN modules
- DC power supply

DALI bus generator



SB2DALI230

- Interfaces the Dupline® bus to standard DALI lighting actuators
- Operates as DALI controller and power supply with possibility to connect up to 64 ballasts to the DALI bus output
- Can be linked to Dupline® at any point in the installation
- Multiple SB2DALI230 units can be connected to the same Dupline® bus

MAIN FEATURES

- Allows the powerful combination of Dupline® and DALI
- Compact dimension: 2-DIN module
- 230 VAC power supply

Universal mobile modem



SH2UMMF124

- Universal modem extension for SH2WEB24
- Connection to SH2WEB24 via internal bus
- Compatibility with quad-band GSM-GPRS-EDGE
- Compatibility with dual-band UMTS-GPRS-HSPA

MAIN FEATURES

- Dimensions: 2-DIN modules
- DC power supply

Digital input module 4 inputs



SH2INDI424

- 4 digital inputs NPN, PNP, voltage free
- The 4 inputs can be configured as contact or counter
- LED indication for power supply, dupline bus, input activated
- Connection to other cabinet modules via local bus

MAIN FEATURES

- Dimensions: 2-DIN modules
- DC power supply

Our product range

Output module solid state relay



SH2SSTRI424

- 4 triac output
- Module load: 4 x 10 W
- LED-indications for supply, bus and outputs status
- Connection to other cabinet modules via local bus
- Push button for local on/off switching

MAIN FEATURES

- Dimensions: 2-DIN modules
- DC power supply

Relay module



SH2RE16A4/SH2RE1A424

- 4 separate outputs relay
- LED-indications for supply, bus and outputs status
- Connection to other cabinet modules via local bus
- Push button for local on/off switching

MAIN FEATURES

- Dimensions: 2-DIN modules
- Bus supplied
- SH2RE16A4: bus supplied
- SH2RE1A424: DC power supply

Relay module



SH2RE16A2E230

- 2 outputs relay
- Energy reading
- LED-indications for supply, bus and outputs status
- Connection to other cabinet modules via local bus
- Push button for local on/off switching

MAIN FEATURES

- Dimensions: 2-DIN modules
- 230 V supplied

Wireless relay with energy reading



SHDWRE16AE230

- Small sized single relay output for eurobox mounting
- Energy reading
- Range up to 100 m in open air
- Load: 16 A/250 VAC

MAIN FEATURES

- Wireless transmission based on IEE802.15.4 @ 2.4 GHz
- Programmable routing function

Decentral output module



BDA-RE13A-U

- Small sized single relay output
- Load: 16 A/250 VAC
- Withstands 130 A inrush current

MAIN FEATURES

- Bus powered

Decentral roller blind module



SHDRODC230

- Up/down control of 1 AC rollerblind motor
- Up/down interlocking for motor
- AC power supply

MAIN FEATURES

- Design for mounting in eurobox
- Relay load 5 A

Home Automation

Our product range

Roller blind modules for AC/DC motor



SH2ROAC224 / SH2RODC224

- Up/down control of 2 AC / DC rollerblind motors
- LED indication for power supply, dupline bus, motor up, motor down
- Connection to other cabinet modules via local bus
- Push button for local on/off switching

MAIN FEATURES

- Dimensions: 2-DIN modules
- DC power supply

Dimmer module with energy reading



SH2D500WE230

- Universal dimmer switch for R, L, C up to 500 W and LED loads
- Integrated heat sink for temperature dissipation
- Energy reading
- Connection to other cabinet modules via local bus
- Push button for local on/off switching

MAIN FEATURES

- Dimensions: 2-DIN modules
- 230 V supplied

Dimmer module up to 500 W



SH2D500W1230

- Universal dimmer switch for R, L, C up to 500 W and LED loads
- Integrated heat sink for temperature dissipation
- Automatic load detection for L, R, C load
- Connection to other cabinet modules via local bus
- Push button for local on/off switching

MAIN FEATURES

- Dimensions: 2-DIN modules
- 230 V supplied

Dimmer module 1-10 V



SH2D10V424

- Switching and dimming adjustable ballasts 1 to 10 V
- 4 independent dimmable outputs
- LED-indications for supply, bus and outputs status
- Connection to other cabinet modules via local bus
- Push button for local on/off switching

MAIN FEATURES

- Dimensions: 2-DIN modules
- DC power supply

Transparent module



SH1DUPFT

- Transparent dupline module
- The dupline bus is present on the top/bottom connectors and internal bus
- Connection to other cabinet modules via local bus

MAIN FEATURES

- Dimensions: 1-DIN module
- No supply is needed

Analogue input modules



SHPINV2T1P124 / SHPINT1P1 SHPINN12 / SHPINV324

- Input modules for thermistor, resistor and voltage measuring
- Ranges: 10 K3 thermistor input, 1-11 K resistor input, 0-10 V input, pt1000/ni1000

MAIN FEATURES

- SHPINV324: three 0-10 V input
- SHPINV2T1P124: two voltage input, one thermistor and one resistor input
- SHPINT1P1: one thermistor and one resistor input
- Bus powered

Our product range

Analogue output module



SHPOUTV224

- Output modules with two 0-10 V outputs
- Small dimensions for decentralized installations

MAIN FEATURES

- DC power supply

Light switch interfaces



BDB-INCON4-U / BDB-IOCON4-U BDB-IOCP8x-U

- Small-sized 4 or 8 I/O modules
- 4 or 8 contact inputs for push buttons

MAIN FEATURES

- Compact housing
- Bus powered

Digital input module



BDD-INCON4-U

- 4 contacts or NPN transistor inputs
- LED-indications for supply and bus status
- LED-indication for armed when using bus supply
- 3-wire system with bus and supply of module through external power supply

MAIN FEATURES

- Open PCB with terminal connection
- Bracket for DIN-rail mounting available

Voltage input module



BDA-INVOL-U

- Input voltage module for building automation
- 1 opto-isolated voltage input 90-265 VAC

MAIN FEATURES

- Compact housing
- Bus powered

Light switches



B4X-LS4-U / B5X-LS4-U

- 4 individually programmable push button inputs
- 4 individually programmable LEDs for true response
- Bus powered, no external supply required

MAIN FEATURES

- B4X-LS4-U: Developed to fit into wall socket and frames from Fuga, NIKO and Bticino
- B5X-LS4-U: Developed to fit into wall socket and frames from Elko, Gira and Jung

Wireless light switches



SHA4XWLS4 / SHE5XWLS4

- 4 individually programmable push buttons
- Blue and red LEDs for wireless field power and battery level
- Battery supplied
- Range up to 100 m in open air

MAIN FEATURES

- SHA4XWLS4: Developed to fit into wall socket and frames from Fuga, NIKO and Bticino
- SHE5XWLS4: Developed to fit into wall socket and frames from Elko, Gira and Jung

Home Automation

Our product range

Glass touch switches



SHG060WLS4 / SHG060BLS4
SHG503WLS6 / SHG503BLS6

- 4 or 6 individually programmable keys
- Black or white glass
- Backlight ON when the hand nears the glass
- Programmable buzzer when a key is pressed
- Integrated temperature sensor, range -9° to 50°C

MAIN FEATURES

- Power supply: 24 VDC
- Mounting: 503 box, Ø60 box

Glass touch dimming



SHG060BSLD / SHG060WSLD
SHG503BSLD / SHG503WSLD

- 4 dimmable outputs or on/off functions. The push buttons can be programmed to control up to
- The dimming level is changed by moving the finger over the slider
- Black or white glass
- Backlight ON when the hand nears the glass
- Programmable buzzer when a key is pressed

MAIN FEATURES

- Power supply: 24 VDC
- Mounting: 503 box, Ø60 box

Glass touch temperature



SHG060BSLT / SHG060WSLT
SHG503BSLT / SHG503WSLT

- It can control one temperature function managing 3 setpoints with the slider and on/off functions
- Integrated temperature sensor, range -9° to 50°C
- White and black glass
- Backlight ON when the hand nears the glass
- Programmable buzzer when a key is pressed
- Shows current room temperature and a secondary temperature

MAIN FEATURES

- Power supply: 24 VDC
- Mounting: 503 box, Ø60 box

90° PIR detectors



B4X-PIR90-U / B5X-PIR90-U

- Passive infrared detector (PIR)
- Detects movement and presence
- Indoor applications
- Operating angle: 90°

MAIN FEATURES

- Bus powered
- Walk test: LED indication
- Programmable sensitivity

90° PIR + lux meters



SHA4XP90L / SHE5XP90L

- Passive infrared detector (PIR)
- Detects movement and presence
- Indoor applications
- Operating angle: 90°
- Lighting measuring range: 0 to 20 K lux

MAIN FEATURES

- Bus powered
- Walk test: LED indication
- Programmable sensitivity

Light switches + 90° PIR + lux meter



SHA4XLS4P90L / SHE5XLS4P90L

- 4 individually programmable push button
- Integrated 90° PIR and luxmeter sensor
- Indoor applications

MAIN FEATURES

- SHA4XLS4P90L: Developed to fit into wall socket and frames from Fuga, NIKO and Bticino
- SHE5XLS4P90L: Developed to fit into wall socket and frames from Elko, Gira and Jung

Our product range

150° PIR detectors



SHE5XP150 / SHA4XP150

- Passive infrared detector (PIR)
- Detects movement and presence
- Indoor and outdoor applications
- Operating angle: 150°
- Operating distance: 8 m

MAIN FEATURES

- Bus powered
- SHA4XP150: Developed to fit into wall socket and frames from Fuga, NIKO and Bticino
- SHE5XP150: Developed to fit into wall socket and frames from Elko, Gira and Jung

150° PIR + lux meters



SHA4XP150L / SHE5XP150L

- Integrated 150° PIR and luxmeter sensor
- Operating angle: 150°
- Operating distance: 8 m

MAIN FEATURES

- SHA4XP150L: Developed to fit into wall socket and frames from Fuga, NIKO and Bticino
- SHE5XP150L: Developed to fit into wall socket and frames from Elko, Gira and Jung

Light switches + temperature and humidity sensor



SHA4XLS4TH / SHE5XLS4TH

- 4 individually programmable push button
- Integrated temperature and humidity sensor
- Temperature range: -40° to 60°C
- Humidity range: 5 to 95 %

MAIN FEATURES

- SHA4XLS4TH: Developed to fit into wall socket and frames from Fuga, NIKO and Bticino
- SHE5XLS4TH: Developed to fit into wall socket and frames from Elko, Gira and Jung

Temperature displays



SHA4XTEMDIS / SHE5XTEMDIS

- Temperature controller with display
- Shows current room, outdoor and auxiliary temperature
- Turns on/off heating and cooling
- Energy Save through 3 different setpoints: comfort, activity, economy

MAIN FEATURES

- Bus powered
- SHA: Developed to fit into wall socket from Fuga, NIKO and Bticino
- SHE: Developed to fit into wall socket from Elko, Gira and Jung

Touch screen/ data logger



BTM-T4-24

- 4" colour display
- Easy setup of graphic pages and functions with the powerful software Wizard
- Activation of internet links through touch buttons
- Support viewing from IP cameras

MAIN FEATURES

- Ethernet connection
- Wide screen display, 64 K colours
- USB port, SD memory, Modbus RTU serial port

Touch screen/ data logger



BTM-T7-24

- 7" colour display
- Easy setup of graphic pages and functions with the powerful software Wizard
- Activation of internet links through touch buttons
- Support viewing from IP cameras

MAIN FEATURES

- Ethernet connection
- Wide screen display, 64 K colours
- USB port, SD memory, Modbus RTU serial port

Home Automation

Our product range

**90° PIR
lux meters**

**90° PIR
lux meters**

**360° PIR
lux meter**



BSD-PIR90-U / SHSDP90L

- Passive infrared detector (PIR)
- Detects movement and presence
- Indoor applications
- Operating distance: 12 m
- Operating angle: 90°

MAIN FEATURES

- Bus powered
- Walk test: LED indication
- Programmable sensitivity



**BSP-PIR90-U / BSP-PIR90A-U
SHSPP90L / SHSPP90LA**

- Passive infrared detector (PIR)
- Detects movement and presence
- Indoor and outdoor applications
- Operating distance: 0.5 - 15 m
- Operating angle: 90°

MAIN FEATURES

- Bus powered
- Programmable sensitivity



SHSQP360L

- Passive infrared detector (PIR)
- Detects movement and presence
- Indoor applications
- Operating distance: ≤7.5 m
- Operating angle: 360°

MAIN FEATURES

- Bus powered
- Programmable sensitivity
- Lens: dual detecting zones

**Environmental
sensors**

**Smoke
detectors**

**Water
detector**



**SHSUXXXXD / SHSUXXXXL
SHSUXXXX**

- Room sensors for CO₂, temperature and humidity measurement
- Available with display, RGB LED or neutral
- Temperature range: -20°C to +50°C
- Humidity range: 0 to 100 %RH
- CO₂ range: 0 to 2000 ppm

MAIN FEATURES

- Easily mountable
- Bus powered
- Low current consumption



BSG-SMO-U / BSG-SMOA-U

- Detection of smouldering and flaming fires with smoke development
- Without radioactive sources
- Detection of up to 60 m²
- Transmission of alarms and Alive signal via bus

MAIN FEATURES

- Battery backup if the connection is interrupted
- Constant monitoring of sensor sensitivity
- Bus powered



BSF-WAT-U

- Integrated water sensor input
- Water resistant PCB with screw terminals
- External input for Felson moisture cable

MAIN FEATURES

- Easily mountable with unique mounting bracket
- Constant monitoring of sensor sensitivity
- Bus powered

Our product range

Wireless window sensors



SHDWWISEN / SHDWWISENIN1

- Dimensions:
sensor: 60 x 30 x 15.5
magnet: 32 x 10.2 x 11.5
- Reed sensor
- Additional voltage free input
- 1 red LED/ 1 blue LED for battery level indication
- Range up to 100 m in open air

MAIN FEATURES

- Wall mounting, crew and double side tape
- Battery supplied

Programmable alarm keypad



BACC-KEYPAD-DC-U

- Keypad for building access control and alarm control
- Indoor or outdoor applications
- 28 user-programmable codes
- Programmable LED indication
- Buzzer output

MAIN FEATURES

- DC power supply

Weather station



SHOWEAGPS

- Light, wind, temperature measurement
- Ranges: 0 to 100K lux, 0 to 35 m/s, -40° to 80°C
- Rain sensor included

MAIN FEATURES

- Integrated GPS receiver
- Modbus RS485 protocol

Anemometer



BSN-ANE-U

- Measuring range: 2 m/s to 25 m/s
- Built-in alarm output with programmable threshold

MAIN FEATURES

- Easily mountable
- Bus powered

Lux meter for outdoor installation



BSH-LUX-U

- Lighting measuring range: 0 to 20K lux
- For indoor and outdoor installation
- Working temperature: -30° to +60°C

MAIN FEATURES

- Easily mountable
- Bus powered

Outdoor temperature sensor



BSI-TEMANAx-U

- Temperature range: -40° to +60°C
- BSI-TEMANA-U is delivered with a M12 plug
- BSI-TEMANAB-U is delivered with 2 m cable

MAIN FEATURES

- Easily mountable
- Bus powered

OUR SALES NETWORK IN EUROPE

AUSTRIA - Carlo Gavazzi GmbH
Ketzergasse 374, A-1230 Wien
Tel: +43 1 888 4112
Fax: +43 1 889 10 53
office@carlogavazzi.at

BELGIUM - Carlo Gavazzi NV/SA
Mechelsesteenweg 311, B-1800 Vilvoorde
Tel: +32 2 257 4120
Fax: +32 2 257 41 25
sales@carlogavazzi.be

DENMARK - Carlo Gavazzi Handel A/S
Over Hadstenvej 40, DK-8370 Hadsten
Tel: +45 89 60 6100
Fax: +45 86 98 15 30
handel@gavazzi.dk

FINLAND - Carlo Gavazzi OY AB
Petaksentie 2-4, FI-00661 Helsinki
Tel: +358 9 756 2000
Fax: +358 9 756 20010
myynti@gavazzi.fi

FRANCE - Carlo Gavazzi Sarl
Zac de Paris Nord II, 69, rue de la Belle
Etoile, F-95956 Roissy CDG Cedex
Tel: +33 1 49 38 98 60
Fax: +33 1 48 63 27 43
french.team@carlogavazzi.fr

GERMANY - Carlo Gavazzi GmbH
Pfnorstr. 10-14
D-64293 Darmstadt
Tel: +49 6151 81000
Fax: +49 6151 81 00 40
info@gavazzi.de

GREAT BRITAIN - Carlo Gavazzi UK Ltd
4.4 Frimley Business Park,
Frimley, Camberley, Surrey GU167SG
Tel: +44 1 276 854110
Fax: +44 1 276 682140
sales@carlogavazzi.co.uk

ITALY - Carlo Gavazzi SpA
Via Milano 13, I-20020 Lainate
Tel: +39 02 931 761
Fax: +39 02 931 763 01
info@gavazziacbu.it

NETHERLANDS - Carlo Gavazzi BV
Wijkemeerweg 23,
NL-1948 NT Beverwijk
Tel: +31 251 22 9345
Fax: +31 251 22 60 55
info@carlogavazzi.nl

NORWAY - Carlo Gavazzi AS
Melkeveien 13, N-3919 Porsgrunn
Tel: +47 35 93 0800
Fax: +47 35 93 08 01
post@gavazzi.no

PORTUGAL - Carlo Gavazzi Lda
Rua dos Jerónimos 38-B,
P-1400-212 Lisboa
Tel: +351 21 361 7060
Fax: +351 21 362 13 73
carlogavazzi@carlogavazzi.pt

SPAIN - Carlo Gavazzi SA
Avda. Iparraguirre, 80-82,
E-48940 Leioa (Bizkaia)
Tel: +34 94 480 4037
Fax: +34 94 431 6081
gavazzi@gavazzi.es

SWEDEN - Carlo Gavazzi AB
V:a Kyrkogatan 1,
S-652 24 Karlstad
Tel: +46 54 85 1125
Fax: +46 54 85 11 77
info@carlogavazzi.se

SWITZERLAND - Carlo Gavazzi AG
Verkauf Schweiz/Vente Suisse
Sumpfstrasse 3,
CH-6312 Steinhausen
Tel: +41 41 747 4535
Fax: +41 41 740 45 40
info@carlogavazzi.ch

OUR SALES NETWORK IN THE AMERICAS

USA - Carlo Gavazzi Inc.
750 Hastings Lane,
Buffalo Grove, IL 60089, USA
Tel: +1 847 465 6100
Fax: +1 847 465 7373
sales@carlogavazzi.com

CANADA - Carlo Gavazzi Inc.
2660 Meadowvale Boulevard,
Mississauga, ON L5N 6M6, Canada
Tel: +1 905 542 0979
Fax: +1 905 542 22 48
gavazzi@carlogavazzi.com

MEXICO - Carlo Gavazzi Mexico S.A. de C.V.
Calle La Montaña no. 28, Fracc. Los Pastores
Naucalpan de Juárez, EDOMEX CP 53340
Tel & Fax: +52.55.5373.7042
mexicosales@carlogavazzi.com

BRAZIL - Carlo Gavazzi Automação Ltda.
Av. Francisco Matarazzo, 1752
Conj 2108 - Barra Funda - São Paulo /SP
CEP 01401-000
Tel: +55 11 3052 0832
Fax: +55 11 3057 1753
info@carlogavazzi.com.br

OUR SALES NETWORK IN ASIA AND PACIFIC

SINGAPORE - Carlo Gavazzi Automation
Singapore Pte. Ltd.
61 Tai Seng Avenue
#05-06 UE Print Media Hub
Singapore 534167
Tel: +65 67 466 990
Fax: +65 67 461 980
info@carlogavazzi.com.sg

MALAYSIA - Carlo Gavazzi Automation
(M) SDN. BHD.
D12-06-G, Block D12,
Pusat Perdagangan Dana 1,
Jalan PJU 1A/46, 47301 Petaling Jaya,
Selangor, Malaysia.
Tel: +60 3 7842 7299
Fax: +60 3 7842 7399
sales@gavazzi-asia.com

CHINA - Carlo Gavazzi Automation
(China) Co. Ltd.
Unit 2308, 23/F.,
News Building, Block 1, 1002
Middle Shennan Zhong Road,
Shenzhen, China
Tel: +86 755 83699500
Fax: +86 755 83699300
sales@carlogavazzi.cn

HONG KONG - Carlo Gavazzi
Automation Hong Kong Ltd.
Unit 3 12/F Crown Industrial Bldg.,
106 How Ming St., Kwun Tong,
Kowloon, Hong Kong
Tel: +852 23041228
Fax: +852 23443689

OUR COMPETENCE CENTRES AND PRODUCTION SITES

DENMARK - Carlo Gavazzi Industri A/S
Hadsten

MALTA - Carlo Gavazzi Ltd
Zejtun

ITALY - Carlo Gavazzi Controls SpA
Belluno

LITHUANIA - Uab Carlo Gavazzi Industri Kaunas
Kaunas

CHINA - Carlo Gavazzi Automation
(Kunshan) Co., Ltd.
Kunshan

HEADQUARTERS

Carlo Gavazzi Automation SpA
Via Milano, 13 - I-20020
Lainate (MI) - **ITALY**
Tel: +39 02 931 761
info@gavazziautomation.com



CARLO GAVAZZI
Automation Components

Energy to Components!

www.gavazziautomation.com

