



## GSM/UMTS/LTE Antennas for REX 100/200/250

MiMo wall antenna, GSM/UMTS/LTE, 4 dBi, incl. 2x 5 m cable, SMA male connectors

- Gain 4 dBi
- 2 x 5 m Cable length
- SMA male connector

For radio reception, a suitable antenna must at least be screwed onto the SMA socket "MAIN" (ANT 2). In order to improve the 4G data throughput, a second antenna terminal is available on the REX 100 LTE router with the SMA socket "Rx" (ANT1). If you would only like to install one antenna, we recommend the MiMo wall antenna, as it already contains two antennas in one housing. Our technical sales is happy to answer any questions you may have regarding the various antennas.

### Technical specifications

General information	
Order number	700-751-ANT35
Article name	MiMo wall antenna, GSM/UMTS/LTE, 4 dBi, 2x 5 m cable, SMA male connectors
Scope of delivery	MiMo wall antenna, incl. cable
Radio networks	LTE 800   GSM 900   GSM 1800, UMTS   LTE 2600
Frequency range	800–960 MHz   1710–2500 MHz   2500–2700 MHz
Radiation pattern	Omni-directional
Gain	2 dBi   5 dBi   4 dBi
VSWR	< 2 : 1
Max. input power	20 W
Impedance	50 Ω
Cable length	5 m; CS29 Coax
Connector type	2x SMA (m)
Antenna	155 mm
Height	186 mm