


PA6 INSULATED END SLEEVES

for flexible Copper conductors

Conductor Size sqmm	Type	Dimensions mm				Insulation Colour	Quantity Box/Bag
		Ø	B	P	L		
0,1÷0,3	PKC306	1,9	1,1	6,0	10,0	light blue	20.000/500
	PKC308	1,9	1,1	8,0	12,0	blue	20.000/500
0,3÷0,5	PKC508	2,6	1,4	8,0	14,0	orange	10.000/500
	PKC510	2,6	1,4	10,0	16,0	orange	10.000/500
0,75	PKC7508	2,8	1,6	8,0	14,0	white	10.000/500
	PKC7512	2,8	1,6	12,0	18,0	white	10.000/500
1	PKC108	3,0	1,8	8,0	14,0	yellow	10.000/500
	PKC112	3,0	1,8	12,0	18,0	yellow	10.000/500
1,5	PKC1508	3,5	2,1	8,0	14,0	red	5.000/500
	PKC1510	3,5	2,1	10,0	16,0	red	7.500/500
	PKC1518	3,5	2,1	18,0	24,0	red	5.000/500
2,5	PKC2508*	4,2	2,6	8,0	14,0	blue	5.000/500
	PKC2512*	4,2	2,6	12,0	18,0	blue	5.000/500
4	PKC2518*	4,2	2,6	18,0	24,0	blue	5.000/500
	PKC410*	4,8	3,3	10,0	18,0	grey	3.000/200
6	PKC412*	4,8	3,3	12,0	20,0	grey	3.000/200
	PKC418*	4,8	3,3	18,0	26,0	grey	3.000/200
10	PKC612	6,3	4,0	12,0	20,0	black	1.500/100
	PKC618	6,3	4,0	18,0	26,0	black	2.000/100
16	PKC1012	7,6	5,0	12,0	22,0	ivory	1.000/100
	PKC1018	7,6	5,0	18,0	28,0	ivory	1.000/100
25	PKC1612	8,8	6,2	12,0	23,0	green	800/100
	PKC1618	8,8	6,2	18,0	29,0	green	1.000/100
35	PKC25016	11,2	7,9	16,0	30,0	brown	500/50
	PKC25022	11,2	7,9	22,0	36,0	brown	500/50
50	PKC35016	12,7	8,9	16,0	30,0	beige	400/50
	PKC35025	12,7	8,9	25,0	39,0	beige	400/50
70	PKC50020	15,0	11,0	20,0	36,0	olive	200/50
	PKC50025	15,0	11,0	25,0	41,0	olive	200/50
95	PKC70022	16,0	14,3	22,0	38,0	yellow	100/25
120	PKC95025	18,0	15,7	25,0	44,0	red	100/25
120	PKC120027	21,0	17,5	27,0	48,0	blue	100/25

*to DIN standard 46 228/4

HF
HALOGEN
FREE



POLYPROPYLENE INSULATED CHAIN END SLEEVES

for flexible Copper conductors

Conductor Size sqmm	Type	Dimensions mm				Insulation Colour	Quantity Box/Bag
		Ø	B	P	L		
0,3÷0,5	CPKD508	2,6	1,3	8,0	14,0	white	5.000
0,75	CPKD7508	2,8	1,5	8,0	14,0	grey	5.000
1	CPKD108	3,0	1,7	8,0	14,0	red	5.000
1,5	CPKD1508	3,5	2,0	8,0	14,0	black	5.000
2,5	CPKD2508	4,2	2,5	8,0	14,0	blue	3.000

Conforms to DIN standard 46228/4.

HF
HALOGEN
FREE



Interchangeable application heads are available for crimping these terminals with the bench press ELB-3 (see page 138).