


PKD

PA6 INSULATED END SLEEVES

for flexible Copper conductors



The PK.. range of end sleeves is manufactured from Tin plated electrolytic Copper.

Designed and developed to reinforce fine wire strands when terminating a cable into a connector block.

The PKD series of insulated end sleeves comply with specification DIN 46228/4.

The operating temperature range is - 20 to + 115°C (Surge + 130°C). Recommended crimping tools are shown on pages 112 to 137, 143-144, 174, 176, 178, 227.

VALSTAR-ND2/PKD

- Comprising:
- a selection of end sleeves PKD conductor size 1-6 sqmm
 - tool ND2.

VALSTAR-ND2/PKE

- Comprising:
- a selection of end sleeves PKE conductor size 1-6 sqmm
 - tool ND2

VALSTAR-ND2/PKC



- Comprising:
- a selection of end sleeves PKC conductor size 1-6 sqmm
 - tool ND2

Conductor Size sqmm	Type	Dimensions mm				Insulation Colour	Quantity Box/Bag
		Ø	B	P	L		
0,3÷0,5	PKD506	2,6	1,4	6,0	12,0	○ white	10.000/500
	PKD508	2,6	1,4	8,0	14,0		10.000/500
	PKD510	2,6	1,4	10,0	16,0		10.000/500
0,75	PKD7506	2,8	1,6	6,0	12,0	● grey	10.000/500
	PKD7508	2,8	1,6	8,0	14,0		10.000/500
	PKD7510	2,8	1,6	10,0	16,0		10.000/500
1	PKD7512	2,8	1,6	12,0	18,0	● red	10.000/500
	PKD106	3,0	1,8	6,0	12,0		10.000/500
	PKD108	3,0	1,8	8,0	14,0		10.000/500
1,5	PKD110	3,0	1,8	10,0	16,0	● black	10.000/500
	PKD112	3,0	1,8	12,0	18,0		10.000/500
	PKD1508	3,5	2,1	8,0	14,0		5.000/500
2,5	PKD1510	3,5	2,1	10,0	16,0	● blue	5.000/500
	PKD1512	3,5	2,1	12,0	18,0		5.000/500
	PKD1518	3,5	2,1	18,0	24,0		5.000/500
4	PKD2508	4,2	2,6	8,0	14,0	● yellow	5.000/500
	PKD2512	4,2	2,6	12,0	18,0		4.000/500
	PKD2518	4,2	2,6	18,0	24,0		5.000/500
6	PKD410	4,8	3,3	10,0	18,0	● grey	3.000/200
	PKD412	4,8	3,3	12,0	20,0		3.000/200
	PKD418	4,8	3,3	18,0	26,0		3.000/200
10	PKD612	6,3	4,0	12,0	20,0	● red	1.500/100
	PKD618	6,3	4,0	18,0	26,0		2.000/100
	PKD1012	7,6	5,0	12,0	22,0		1.000/100
16	PKD1018	7,6	5,0	18,0	28,0	● blue	1.000/100
	PKD1612	8,8	6,4	12,0	24,0		800/100
	PKD1618	8,8	6,4	18,0	28,0		1.000/100
25	PKD25016	11,2	7,9	16,0	30,0	● yellow	500/50
	PKD25022	11,2	7,9	22,0	36,0		500/50
	PKD35016	12,7	8,9	16,0	30,0		400/50
35	PKD35025	12,7	8,9	25,0	39,0	● red	400/50
	PKD50020	15,0	11,0	20,0	36,0		200/50
	PKD50025	15,0	11,0	25,0	41,0		200/50

PKE

PA6 INSULATED END SLEEVES

for flexible Copper conductors



Conductor Size sqmm	Type	Dimensions mm				Insulation Colour	Quantity Box/Bag
		Ø	B	P	L		
0,1÷0,3	PKE308	1,9	1,1	8,0	12,0	● yellow	20.000/500
0,3÷0,5	PKE508*	2,6	1,4	8,0	14,0	○ white	10.000/500
0,75	PKE7508	2,8	1,6	8,0	14,0	● blue	5.000/500
1	PKE108*	3,0	1,8	8,0	14,0	● red	6.000/500
	PKE1508*	3,5	2,1	8,0	14,0		5.000/500
1,5	PKE1510*	3,5	2,1	10,0	16,0	● black	5.000/500
	PKE1518*	3,5	2,1	18,0	24,0		5.000/500
2,5	PKE2508	4,2	2,6	8,0	14,0	● grey	5.000/500
	PKE2512	4,2	2,6	12,0	18,0		5.000/500
	PKE2518	4,2	2,6	18,0	24,0		3.000/500
4	PKE410	4,8	3,3	10,0	18,0	● orange	3.000/200
	PKE412	4,8	3,3	12,0	20,0		3.000/200
	PKE418	4,8	3,3	18,0	26,0		3.000/200
6	PKE612	6,3	4,0	12,0	20,0	● green	1.500/100
	PKE618	6,3	4,0	18,0	26,0		2.000/100
10	PKE1012	7,6	5,0	12,0	22,0	● brown	1.000/100
	PKE1018	7,6	5,0	18,0	28,0		1.000/100
16	PKE1612	8,8	6,2	12,0	23,0	○ ivory	800/100
	PKE1618	8,8	6,2	18,0	29,0		1.000/100
25	PKE25016	11,2	7,9	16,0	30,0	● black	500/50
	PKE25022	11,2	7,9	22,0	36,0		500/50

*to DIN standard 46 228/4