



Type PKT range of end sleeves is manufactured from Tin plated electrolytic Copper. Designed to accommodate two cables terminating in the same sleeve. The operating temperature range is -20 to +115°C (Surge +130°C).

Recommended crimping tools are shown on pages 112 to 137, 143-144, 174, 176, 178, 227.

Conductor Size sqmm	Type	Dimensions mm				Insulation Colour	ND1,ND2,ND3, ND4 and HNKE 50 Compression Aperture	Quantity Box/Bag
		C	B	P	L			
2 x 0,5	PKT508	4,7x2,6	1,8	8,0	14,0	○ white	1	5.000/500
	PKT510*	4,7x2,6	1,8	10,0	18,0			5.000/500
2 x 0,75	PKT7508	5,0x2,8	2,1	8,0	15,0	● grey	1,5	2.500/100
	PKT7510	5,0x2,8	2,1	10,0	17,0			2.500/100
2 x 1	PKT108	5,4x3,4	2,4	8,0	16,0	● red	2,5	2.500/100
	PKT110	5,4x3,4	2,4	10,0	18,0			2.500/100
2 x 1,5	PKT1508	6,6x3,6	2,6	8,0	16,0	● black	2,5	2.500/100
	PKT1512	6,6x3,6	2,6	12,0	20,0			2.500/100
2 x 2,5	PKT2510	7,8x4,2	3,2	10,0	20,0	● blue	4	2.000/100
	PKT2512	7,8x4,2	3,2	12,0	22,0			1.500/100
2 x 4	PKT412	8,8x4,9	4,2	12,0	23,0	● grey	6	1.000/100
2 x 6	PKT614	10,0x6,9	5,3	14,0	26,0	● yellow	10	800/100
2 x 10	PKT1014	13,3x7,5	6,2	12,0	24,0	● red	16	500/50
2 x 16	PKT1614	18,6x9,6	8,9	14,0	30,0	● blue	35	300/50

\*Not UL approved