

Pneumo-hydraulic with interchangeable dies



Pneumo-hydraulic, production bench press, controlled by a foot operated pedal, provides a consistent and reliable crimped connection. Extensive range of interchangeable dies available for crimping a wide variety of connectors.

NOTE: for applications not listed, please contact Cembre.



PNB-1 detail of the crimping zone with PU-1 guard.

### TECHNICAL FEATURES

Nominal operating pressure	6 bar
----------------------------	-------

### Dimensions mm

Width	180
Depth	320
Height	700
Weight kg (without dies)	23

### INTERCHANGEABLE DIES (to be ordered separately)

Die Set	Guard*	Connector Type			Nominal Conductor Size sqmm			
PV-1	PU-1	Insulated Connectors	green	0,2÷0,5				
PR-1			red	0,25÷1,5				
PB-1			blue	1,5÷2,5				
PG-1			yellow	4÷6				
PH1-1	PH-1**	Through connectors PE HD insulated		0,5÷6				
		NL-M, NL-P connectors PA6.6 insulated		0,25÷6				
KE0.75-1	PK-1	End Sleeves	KE, PK...	0,3 - 0,5 - 0,75				
KE2.5-1				1 - 1,5 - 2,5				
KE10-1				4 - 6 - 10				
MTT16-50	ME-1			16				
MTT25-50				25				
N1-1	PU-1	A 03-M..	S 1.5-..	RN-..	0,25 - 1,5			
		A 06-M..	S 2.5-..	BN-..	1,5 - 2,5			
		A 1-M..	S 6-..	GN-..	4 - 6			
ME1-50	ME-1	Uninsulated Copper Lugs		A1-M..	4 - 6			
ME2-50				A2-M.. S10-M..	10			
ME3-50				A3-M..	16			
ME5-50				A5-M..	25			
ME7-50				A7-M..	35			
ME9-50				A9-M..				
ME10-50				A10-M..	50			
ME12-50				A12-M..				
MN2RF-50				MN RF-1	Polyamide Insulated Lugs		ANE2-M..	10
MN3RF-50							ANE3-M..	16
MN5RF-50	ANE5-M..	25						
MN7RF-50	ANE7-M..							
	ANE9-M..	35						

\* Supplied as standard with the machine \*\* Supplied as standard with the die