

# Professional SCREWDRIVERS

The Cembre range of insulated screwdrivers have dual compound handgrips and an ergonomic design making them particularly practical and comfortable in the following modes of use:

- Normal
- Fast
- Forced

To ensure quick identification, the type and size of the head are indicated in different colours on the back of the handle.

The heads are made from Chromium Molybdenum steel with a hardness of 55-59 HRC and are hardened with Phosphoric Manganese Acid to increase corrosion resistance; the size of the insulating cover allows it to be inserted into tight spaces.

Each individual screwdriver is tested in accordance with EN 60900



**1000V**  
EN/IEC - 60900



Blade type identification on the back of the handle



Chromium Molybdenum steel head with hardness 55-59 HRC and anti-corrosion surface treatment

Narrow insulating cover to allow insertion into tight spaces

Soft and durable hand guard

Shaped blade for greater resistance and stability

Ergonomic and shaped hand grip

Coating in dual compound plastic material with soft rubber inserts



- Head type identification codes:
- **White** - Flat head
  - **Yellow** - "Phillips" cross head
  - **Green** - "Pozidriv" cross head
  - **Red** - "Phillips" combination head
  - **Blue** - "Pozidriv" combination head

Steel tips



Ergonomic handle



Hand guard



Attachment hole

**Hex socket screwdrivers with reduced shank diameter**



**Main Features**

Model	Dimensions Socket mm	Blade Length mm	Total Length mm	Weight g
<b>SDC 7 X 125-HEX</b>	7	125	243	97
<b>SDC 8 X 125-HEX</b>	8	125	243	114
<b>SDC 9 X 125-HEX</b>	9	125	243	132
<b>SDC 10 X 125-HEX</b>	10	125	243	152

**Hex socket screwdrivers with reduced shank diameter.**

- Ergonomic handgrip for comfortable use without strain.
- Reduced external shank diameter allows the tool to be used in narrow spaces (relays and switches).
- Deep point socket ideal for long threads.
- Hexagonal lever point facilitates extra force without strain.
- Standards: ISO 6750 - ISO 2236



Deep point socket



Hexagonal lever point

Reduced shank diameter



**Universal key for switchboards UKC4**

**Main Features**

Model	Dimensions mm			Weight g
	Length	Width	Height	
<b>UKC4</b>	72	72	14	92

Universal key for switchboards

Equipped with:

Triangular shape 7-8 mm

Double notch 3-5 mm

Square shape 5-6, 7-8 mm

Screwdriver bit and hexagonal holder

