MECHANICAL TOOLS TND RANGE

for uninsulated terminals and connectors according to DIN 46235 and DIN 46267 T.1

Mechanical tools equipped with rotating dies with hexagonal imprint compliant with DIN 480863 suitable to crimp Copper lugs according to DIN 46235 and through connectors according to DIN 46267 T.1 (refer to page 40-41), particularly sturdy and easy to handle.



| 6lan | |
|------|----|
| | H |
| | П |
| 0 | ×. |

TECHNICAL FEATURES

| 10 10 10 | Crimping Ran |
|-----------|---------------------|
| | Dimensions m |
| | Length |
| ()Cembre | Width |
| TND6 - 70 | Height |
| | Weight kg |
| | |

| Crimping Range | Uninsulated terminals and connectors according to DIN 46235 and DIN 46267 T.1 for conductor sizes 6 to 70 sqmm |
|----------------|--|
| Dimensions mm | |
| Length | 515 |
| Width | 132 |
| Height | 46 |
| Weight kg | 2 |



MECHANICAL TOOLS TND RANGE

for uninsulated terminals and connectors according to DIN 46235 and DIN 46267 T.1



Mechanical tools equipped with rotating dies with hexagonal imprint compliant with DIN 480863 suitable to crimp Copper lugs according to DIN 46235 and through connectors according to DIN 46267 T.1 (refer to page 40-41), particularly sturdy and easy to handle.



TECHNICAL FEATURES

Crimping Range

Uninsulated terminals and connectors according to DIN 46235 and DIN 46267 T.1 for conductor sizes 10 to 120 mm²

| Dimensions mm | |
|---------------|-----|
| Length | 665 |
| Width | 162 |
| Height | 52 |
| Weight kg | 3,7 |
| | |